# Logical Relations for Call-by-value $\lambda$-calculus with Shift and Reset

Kenichi Asai *

Ochanomizu University
2-1-1 Otsuka Bunkyo-ku Tokyo 112-8610 Japan
asai@is.ocha.ac.jp

## Abstract

Logical relations, defined inductively on the structure of types, provide a powerful tool to characterize higher-order functions. They often enable us to prove correctness of a program transformer written with higher-order functions concisely. This paper demonstrates that the technique of logical relations can be used to characterize call-by-value functions as well as delimited continuations. Based on the traditional logical relations for call-by-name functions, logical relations for call-by-value functions are first defined, which are used to prove the correctness of an offline specializer for the call-by-value $\lambda$-calculus. They are then modified to cope with delimited continuations and are used to establish the correctness of an offline specializer for the call-by-value $\lambda$-calculus with delimited continuation constructs, shift and reset. This is the first correctness proof for such a specializer. Along the development, correctness of the continuation-based and shift/reset-based let-insertion and A-normalization is established. As another application of the logical relations, a direct proof of the strong normalization for the typed call-by-value $\lambda$-calculus with shift and reset is shown. Thanks to the natural definition of logical relations, the proof is simple even with the presence of shift and reset.

***keywords*** Logical relations, offline specialization, delimited continuations, correctness, type systems, let-insertion, A-normalization

## 1. Introduction

Whenever we build a program transformer, be it a compiler, an optimizer, or a specializer, we need to establish its correctness. We have to show that the semantics of a program does not change before and after the transformation. As a program transformer gets sophisticated, however, it becomes harder to prove its correctness. In particular, the non-trivial use of higher-order functions in the transformer makes the correctness proof particularly difficult. A simple structural induction on the input program does not usually work, because we can not easily characterize their behavior.

The technique of logical relations [16] is one of the proof methods that is often used in such a case. With the help of types, it enables us to define a set of relations that captures necessary properties of higher-order functions. Notably, Wand [22] used this technique to prove correctness of an offline specializer [13] in which higher-order

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. To copy otherwise, to republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee.

*submitted for publication* date, City.

Copyright © 2005 ACM supplied by printer. . . $5.00.

* Most of the work has been done while the author was visiting Northeastern University. Special thanks to Mitch Wand for hosting my stay.

functions rather than closures were used for the representation of abstractions. However, the logical relations used by Wand were for call-by-name functions. They were used to prove the correctness of a specializer for the call-by-name $\lambda$-calculus, but are not directly applicable to the call-by-value languages.

In this paper, we demonstrate that the technique of logical relations can be used to characterize call-by-value functions as well as delimited continuations. We first modify Wand's logical relations so that we can use them for call-by-value functions. We then prove the correctness of an offline specializer for the call-by-value $\lambda$-calculus. It is written in continuation-passing style (CPS) and uses the continuation-based let-insertion to avoid computation elimination/duplication.

It is well-known that by using delimited continuation constructs, *shift* and *reset*, introduced by Danvy and Filinski [7], it is possible to implement the let-insertion in direct style [19, 20]. We demonstrate that the correctness of this direct-style specializer with the shift/reset-based let-insertion can be also established by properly characterizing delimited continuations in logical relations.

Then, the specializer is extended to cope with shift and reset in the source language. To this end, the specialization-time delimited continuations are used to implement the delimited continuations in the source language. To characterize such delimited continuations, we define logical relations based on Danvy and Filinski's type system [6]. Thanks to the explicit reference to the types of continuations and the final result, we can establish the correctness of the specializer. This is the first correctness proof for the offline specializer for the call-by-value $\lambda$-calculus with shift and reset. The present author previously showed the correctness of a similar offline specializer [3], but it produced the result of specialization in CPS.

The basic idea behind the logical relations shown in this paper is not restricted to proving the correctness of specializers. As another application of the logical relations, a direct proof of the strong normalization for the typed call-by-value $\lambda$-calculus with shift and reset is shown. Thanks to the natural definition of logical relations, the proof is simple even with the presence of shift and reset. Previously, this result was shown only indirectly by embedding shift and reset into a strongly normalizing calculus called $\lambda_{\overrightarrow{C}}^{-}$-calculus [1].

The contributions of this paper are summarized as follows:

- We show that the technique of logical relations can be used to characterize call-by-value functions as well as delimited continuations.
- We show for the first time the correctness of the offline specializer for the call-by-value $\lambda$-calculus with shift and reset.
- Along the development, we establish the correctness of the continuation-based let-insertion, the shift/reset-based let-insertion, the continuation-based A-normalization [11], and the shift/reset-based A-normalization.
- We show a direct proof of the strong normalization for the typed call-by-value $\lambda$-calculus with shift and reset.

The paper is organized as follows. After showing preliminaries in Section 2, the call-by-name specializer and its correctness proof by Wand are reviewed in Section 3. We then show the logical relations for call-by-value functions in Section 4, and use them to prove the correctness of a specializer for the call-by-value $\lambda$-calculus in Section 5. In Section 6, we transform the specializer into direct style and prove its correctness. Then, we further extend the specializer to cope with shift and reset. We show an interpreter and an A-normalizer in Section 7, a specializer in Section 8, a type system in Section 9, and logical relations with which the correctness is established in Section 10. Section 11 proves the strong normalization for the typed call-by-value $\lambda$-calculus with shift and reset. Related work is in Section 12 and the paper concludes in Section 13. For interested reviewers, the appendix contains a complete proof of correctness of the offline specializer for shift and reset.

## 2. Preliminaries

The input language to our specializer is a $\lambda$-calculus extended with shift and reset. Its syntax is defined as follows:

$$M = x \mid \lambda x.\, M \mid M \mathbin{@} M \mid \xi k.\, M \mid \langle M \rangle$$

The last two terms represent shift and reset, respectively, and appear only later in the paper. Their intuitive meaning is briefly described below. We use $\boldsymbol{M}$ (possibly with a subscript) to range over the input terms. We use a bold font to emphasize that they are data manipulated by programs, such as an interpreter and a specializer. In OCaml, for example, the input terms can be represented by the following type:

```
type term = Var of string | Lam of string * term | App of term * term
          | Shift of string * term | Reset of term
```

When the input language is processed through a binding-time analysis, each term is annotated with either static or dynamic. The syntax for the annotated term is defined as follows:

$$\boldsymbol{W} \;=\; \boldsymbol{x} \mid \overline{\boldsymbol{\lambda}}\boldsymbol{x}.\,\boldsymbol{W} \mid \underline{\boldsymbol{\lambda}}\boldsymbol{x}.\,\boldsymbol{W} \mid \boldsymbol{W}\,\overline{@}\,\boldsymbol{W} \mid \boldsymbol{W}\,\underline{@}\,\boldsymbol{W} \mid \overline{\boldsymbol{\xi}}\boldsymbol{k}.\,\boldsymbol{W} \mid \underline{\boldsymbol{\xi}}\boldsymbol{k}.\,\boldsymbol{W} \mid \overline{\langle \boldsymbol{W} \rangle} \mid \underline{\langle \boldsymbol{W} \rangle}$$

As usual, we use overlines and underlines to indicate static and dynamic expressions, respectively. $\boldsymbol{W}$ is used to range over the annotated terms. We call both $\boldsymbol{M}$ and $\boldsymbol{W}$ the baselanguage.

The metalanguage that is used to define specializers is a standard functional language whose core syntax is defined using a standard font as follows:

$$\begin{array}{rcl} M, K & = & x \mid \lambda x.\,M \mid M\,M \mid \xi k.\,M \mid \langle M \rangle \mid \\ & & \boldsymbol{x} \mid \boldsymbol{\lambda}\boldsymbol{x}.\,M \mid M\,@\,M \mid \boldsymbol{\xi}\boldsymbol{k}.\,M \mid \langle\!\langle M \rangle\!\rangle \mid \\ & & \overline{\boldsymbol{\lambda}}\boldsymbol{x}.\,M \mid \underline{\boldsymbol{\lambda}}\boldsymbol{x}.\,M \mid M\,\overline{@}\,M \mid M\,\underline{@}\,M \mid \overline{\boldsymbol{\xi}}\boldsymbol{k}.\,M \mid \underline{\boldsymbol{\xi}}\boldsymbol{k}.\,M \mid \overline{\langle\!\langle M \rangle\!\rangle} \mid \underline{\langle\!\langle M \rangle\!\rangle} \end{array}$$

We use juxtaposition without @ for application ($M\,M$). We assume that the metalanguage has shift ($\xi k.\,M$) and reset ($\langle M \rangle$) operations. Their implementation using call/cc is available for Scheme [15], Standard ML [10], and OCaml. For Scheme, there is also a direct implementation [12]. We also assume that the metalanguage has a way to represent the baselanguage terms, like the `term` datatype above ($\boldsymbol{x}, \cdots, \underline{\langle\!\langle M \rangle\!\rangle}$). We share the same $\boldsymbol{x}$ for both unannotated and annotated terms, but they can be made separate. We usually use $M$ to range over the metalanguage terms, but $K$ is also used for the body of continuations.

Among the metalanguage terms, we refer to the following terms as values:

$$\begin{array}{rcl} V & = & x \mid \lambda x.\,M \mid \\ & & \boldsymbol{x} \mid \boldsymbol{\lambda}\boldsymbol{x}.\,V \mid V\,@\,V \mid \boldsymbol{\xi}\boldsymbol{k}.\,V \mid \langle\!\langle V \rangle\!\rangle \mid \\ & & \overline{\boldsymbol{\lambda}}\boldsymbol{x}.\,V \mid \underline{\boldsymbol{\lambda}}\boldsymbol{x}.\,V \mid V\,\overline{@}\,V \mid V\,\underline{@}\,V \mid \overline{\boldsymbol{\xi}}\boldsymbol{k}.\,V \mid \underline{\boldsymbol{\xi}}\boldsymbol{k}.\,V \mid \overline{\langle\!\langle V \rangle\!\rangle} \mid \underline{\langle\!\langle V \rangle\!\rangle} \end{array}$$

In addition to the variables ($x$) and abstractions ($\lambda x.\,M$) in the metalanguage, constructors for the baselanguage applied to values are included. In short, everything that is a value in a functional language with datatypes is a value. $V$ is used to range over the values.

Given an input term represented as a value, a transformer (written in the metalanguage) manipulates it and produces another value, *i.e.*, a result term. For example, $\lambda x.\,x$ is an identity transformer. Given a term $(\boldsymbol{\lambda}\boldsymbol{x}.\,\boldsymbol{x})@(\boldsymbol{\lambda}\boldsymbol{y}.\,\boldsymbol{y})$, it produces the output that is identical to the input:

$$(\lambda x.\,x)\,((\boldsymbol{\lambda}\boldsymbol{x}.\,\boldsymbol{x})@(\boldsymbol{\lambda}\boldsymbol{y}.\,\boldsymbol{y})) \quad \sim_v \quad (\boldsymbol{\lambda}\boldsymbol{x}.\,\boldsymbol{x})@(\boldsymbol{\lambda}\boldsymbol{y}.\,\boldsymbol{y})$$

In OCaml, this is represented as:

```
# (fun x -> x) (App (Lam ("x", Var ("x")), Lam ("y", Var ("y"))));;
- : term = App (Lam ("x", Var "x"), Lam ("y", Var "y"))
#
```

Although the metalanguage is written in the form similar to the $\lambda$-calculus, we intend it to be a standard functional language, such as OCaml. In particular, we use recursion and a case dispatch on the baselanguage terms in the style of denotational semantics.

Throughout this paper, we use three kinds of equalities between terms in the metalanguage: $=$ for definition or $\alpha$-equality, $\sim_n$ for $\beta$-equality under call-by-name semantics, and $\sim_v$ for $\beta$-equality under call-by-value semantics. The call-by-value $\beta$-equality in the presence of shift and reset is defined by Kameyama and Hasegawa [14].

***Shift and Reset*** Intuitively, a shift expression $\xi k.\, M$ takes its current continuation up to its enclosing reset, binds it to $k$, and discards the current continuation with which the whole shift expression was called. For example, in the expression $1 + \langle 10 + \xi k.\, k\,(k\,100)\rangle$, $k$ is bound to a continuation $\lambda v.\, 10 + v$. Applying it twice to 100 yields 120, the continuation $\langle 10 + \cdot\rangle$ is discarded, the value of $\langle 10 + \xi k.\, k\,(k\,100)\rangle$ is thus 120, and the final result is 121. The precise semantics of shift and reset is typically given by a CPS interpreter or by CPS transformation [7].

## 3. Specializer for Call-by-name $\lambda$-calculus

In this section, we review the specializer for the call-by-name $\lambda$-calculus and its correctness proof using the technique of logical relations presented by Wand [22].

A specializer consists of two parts: an interpreter for static expressions and a residualizer for dynamic expressions. An interpreter for the input language is defined as follows:

$$\begin{array}{rcl}
\mathcal{I}_1\,[\![\boldsymbol{x}]\!]\,\rho & = & \rho\,(\boldsymbol{x}) \\
\mathcal{I}_1\,[\![\boldsymbol{\lambda x.\, M}]\!]\,\rho & = & \lambda x.\, \mathcal{I}_1\,[\![\boldsymbol{M}]\!]\,\rho[x/\boldsymbol{x}] \\
\mathcal{I}_1\,[\![\boldsymbol{M_1 \mathbin{@} M_2}]\!]\,\rho & = & (\mathcal{I}_1\,[\![\boldsymbol{M_1}]\!]\,\rho)\,(\mathcal{I}_1\,[\![\boldsymbol{M_2}]\!]\,\rho)
\end{array}$$

where $\rho[x/\boldsymbol{x}]$ is the same environment as $\rho$ except that $\rho\,(\boldsymbol{x}) = x$.

The residualizer is almost the identity function except for the renaming of variables to avoid name clashes:

$$\begin{array}{rcl}
\mathcal{D}_1\,[\![\boldsymbol{x}]\!]\,\rho & = & \rho\,(\boldsymbol{x}) \\
\mathcal{D}_1\,[\![\boldsymbol{\lambda x.\, M}]\!]\,\rho & = & \boldsymbol{\lambda x^{\diamond}.}\,\mathcal{D}_1\,[\![\boldsymbol{M}]\!]\,\rho[\boldsymbol{x^{\diamond}}/\boldsymbol{x}] \\
\mathcal{D}_1\,[\![\boldsymbol{M_1 \mathbin{@} M_2}]\!]\,\rho & = & (\mathcal{D}_1\,[\![\boldsymbol{M_1}]\!]\,\rho)\boldsymbol{@}(\mathcal{D}_1\,[\![\boldsymbol{M_2}]\!]\,\rho)
\end{array}$$

A variable with the superscript $^{\diamond}$ indicates that it is a fresh variable (produced by gensym).

An offline specializer is given by putting the interpreter and the residualizer together:

$$\begin{array}{rcl}
\mathcal{P}_1\,[\![\boldsymbol{x}]\!]\,\rho & = & \rho\,(\boldsymbol{x}) \\
\mathcal{P}_1\,[\![\boldsymbol{\overline{\lambda} x.\, W}]\!]\,\rho & = & \lambda x.\, \mathcal{P}_1\,[\![\boldsymbol{W}]\!]\,\rho[x/\boldsymbol{x}] \\
\mathcal{P}_1\,[\![\boldsymbol{\underline{\lambda} x.\, W}]\!]\,\rho & = & \boldsymbol{\lambda x^{\diamond}.}\,\mathcal{P}_1\,[\![\boldsymbol{W}]\!]\,\rho[\boldsymbol{x^{\diamond}}/\boldsymbol{x}] \\
\mathcal{P}_1\,[\![\boldsymbol{W_1 \mathbin{\overline{@}} W_2}]\!]\,\rho & = & (\mathcal{P}_1\,[\![\boldsymbol{W_1}]\!]\,\rho)\,(\mathcal{P}_1\,[\![\boldsymbol{W_2}]\!]\,\rho) \\
\mathcal{P}_1\,[\![\boldsymbol{W_1 \mathbin{\underline{@}} W_2}]\!]\,\rho & = & (\mathcal{P}_1\,[\![\boldsymbol{W_1}]\!]\,\rho)\boldsymbol{@}(\mathcal{P}_1\,[\![\boldsymbol{W_2}]\!]\,\rho)
\end{array}$$

The specializer goes wrong if the input term is not well-annotated. Well-annotatedness of a term is specified as a binding-time analysis that, given an unannotated term, produces a well-annotated term. Here, we show a type-based binding-time analysis. Define binding-time types of expressions as follows:

$$\tau \;=\; d \mid \tau \to \tau$$

An expression of type $d$ denotes that the expression is dynamic, while an expression of type $\sigma \to \tau$ shows that it is a static function. (We do not need a type $s$ for static constants, because our baselanguage does not have any constants. It is straightforward to include them.) We use a judgment of the form $A \vdash \boldsymbol{M} : \tau\ [\boldsymbol{W}]$, which reads: under a type environment $A$, a term $\boldsymbol{M}$ has a binding-time type $\tau$ and is annotated as $\boldsymbol{W}$. The binding-time

analysis is defined as the following typing rules:

$$A[\boldsymbol{x} : \tau] \vdash \boldsymbol{x} : \tau\ [\boldsymbol{x}]$$

$$\frac{A[\boldsymbol{x} : \sigma] \vdash \boldsymbol{M} : \tau\ [\boldsymbol{W}]}{A \vdash \boldsymbol{\lambda x.\, M} : \sigma \to \tau\ [\overline{\boldsymbol{\lambda}}\boldsymbol{x.\, W}]}$$

$$\frac{A[\boldsymbol{x} : d] \vdash \boldsymbol{M} : d\ [\boldsymbol{W}]}{A \vdash \boldsymbol{\lambda x.\, M} : d\ [\underline{\boldsymbol{\lambda}}\boldsymbol{x.\, W}]}$$

$$\frac{A \vdash \boldsymbol{M_1} : \sigma \to \tau\ [\boldsymbol{W_1}] \quad A \vdash \boldsymbol{M_2} : \sigma\ [\boldsymbol{W_2}]}{A \vdash \boldsymbol{M_1 @ M_2} : \tau\ [\boldsymbol{W_1}\ \overline{\boldsymbol{@}}\ \boldsymbol{W_2}]}$$

$$\frac{A \vdash \boldsymbol{M_1} : d\ [\boldsymbol{W_1}] \quad A \vdash \boldsymbol{M_2} : d\ [\boldsymbol{W_2}]}{A \vdash \boldsymbol{M_1 @ M_2} : d\ [\boldsymbol{W_1}\ \underline{\boldsymbol{@}}\ \boldsymbol{W_2}]}$$

To show the correctness of the specializer, Wand [22] uses the technique of logical relations. Define logical relations between terms in the metalanguage by induction on the structure of binding-time types as follows:

$$\begin{array}{lcl} (M, M') \in \boldsymbol{R}_d & \iff & \mathcal{I}_1\,[\![M]\!]\,\rho_{id} \sim_n M' \\ (M, M') \in \boldsymbol{R}_{\sigma\to\tau} & \iff & \forall (N, N') \in \boldsymbol{R}_\sigma.\ (M\ N, M'\ N') \in \boldsymbol{R}_\tau \end{array}$$

where $\rho_{id}(\boldsymbol{x}) = x$ for all $\boldsymbol{x}$. It relates free variables in the base- and metalanguage. In the definition of $\boldsymbol{R}_d$, $M$ is a metalanguage term that is either a value representing a baselanguage term or a term that is equal to (or evaluates to) a value representing a baselanguage term in the underlying semantics of the metalanguage (in this section, call-by-name). The semantic brackets are usually used to enclose syntactic objects only, but here we use them to enclose a term that evaluates to a syntactic object.

For environments $\rho$ and $\rho'$, we say $(\rho, \rho') \models A$ iff for all $\boldsymbol{x} \in \mathit{dom}(A)$, $(\rho\,(\boldsymbol{x}), \rho'\,(\boldsymbol{x})) \in \boldsymbol{R}_{A(\boldsymbol{x})}$, where $\mathit{dom}(A)$ is the domain of $A$. Then, we can show the following theorem:

THEOREM 1 (Wand [22]). *If* $A \vdash \boldsymbol{M} : \tau\ [\boldsymbol{W}]$ *and* $(\rho, \rho') \models A$, *then* $(\mathcal{P}_1\,[\![\boldsymbol{W}]\!]\,\rho, \mathcal{I}_1\,[\![\boldsymbol{M}]\!]\,\rho') \in \boldsymbol{R}_\tau$.

By instantiating it to an empty environment $\rho_\phi$, we obtain the following corollary, which establishes the correctness of specialization.

COROLLARY 1 (Wand [22]). *If* $\vdash \boldsymbol{M} : d\ [\boldsymbol{W}]$, *then* $\mathcal{I}_1\,[\![\mathcal{P}_1\,[\![\boldsymbol{W}]\!]\,\rho_\phi]\!]\,\rho_{id} \sim_n \mathcal{I}_1\,[\![\boldsymbol{M}]\!]\,\rho_\phi$.

The proof of Theorem 1 proceeds by induction on the structure of the proof of $A \vdash \boldsymbol{M} : \tau\ [\boldsymbol{W}]$. Since there are five typing rules for this judgment, the proof is split into five cases. Among them, the logical relations play an important role in the case for static applications. Let us review this case. We will later see how this case fails for the call-by-value semantics.

***Proof Case (Static Application)*** Assume

$$\frac{A \vdash \boldsymbol{M_1} : \sigma \to \tau\ [\boldsymbol{W_1}] \quad A \vdash \boldsymbol{M_2} : \sigma\ [\boldsymbol{W_2}]}{A \vdash \boldsymbol{M_1 @ M_2} : \tau\ [\boldsymbol{W_1}\ \overline{\boldsymbol{@}}\ \boldsymbol{W_2}]}$$

We must show

$$(\mathcal{P}_1\,[\![\boldsymbol{W_1}\ \overline{\boldsymbol{@}}\ \boldsymbol{W_2}]\!]\,\rho, \mathcal{I}_1\,[\![\boldsymbol{M_1 @ M_2}]\!]\,\rho') \in \boldsymbol{R}_\tau$$

assuming $(\rho, \rho') \models A$. By the definition of $\mathcal{P}_1$ and $\mathcal{I}_1$, it suffices to show

$$((\mathcal{P}_1\,[\![\boldsymbol{W_1}]\!]\,\rho)\,(\mathcal{P}_1\,[\![\boldsymbol{W_2}]\!]\,\rho), (\mathcal{I}_1\,[\![\boldsymbol{M_1}]\!]\,\rho')\,(\mathcal{I}_1\,[\![\boldsymbol{M_2}]\!]\,\rho')) \in \boldsymbol{R}_\tau\ .$$

By the induction hypotheses, we have

$$(\mathcal{P}_1 [\![\boldsymbol{W_1}]\!] \rho, \mathcal{I}_1 [\![\boldsymbol{M_1}]\!] \rho') \in R_{\sigma\to\tau}$$

and

$$(\mathcal{P}_1 [\![\boldsymbol{W_2}]\!] \rho, \mathcal{I}_1 [\![\boldsymbol{M_2}]\!] \rho') \in R_{\sigma} \ .$$

Thus, *from the definition of $R_{\sigma\to\tau}$, we have*

$$((\mathcal{P}_1 [\![\boldsymbol{W_1}]\!] \rho)\,(\mathcal{P}_1 [\![\boldsymbol{W_2}]\!] \rho), (\mathcal{I}_1 [\![\boldsymbol{M_1}]\!] \rho')\,(\mathcal{I}_1 [\![\boldsymbol{M_2}]\!] \rho')) \in R_{\tau} \ ,$$

which proves the theorem for this case. □

The crucial part appears at the end of the proof. The last derivation relies on the definition of $R_{\sigma\to\tau}$ showing that $\mathcal{P}_1 [\![\boldsymbol{W_1}]\!] \rho$ and $\mathcal{I}_1 [\![\boldsymbol{M_1}]\!] \rho'$ transform the related arguments to the related results.

The use of logical relations is essential here. It might appear at first that we could prove $\mathcal{I}_1 [\![\mathcal{P}_1 [\![\boldsymbol{W}]\!] \rho]\!] \rho_{id} \sim_n \mathcal{I}_1 [\![\boldsymbol{M}]\!] \rho'$ directly by induction on the structure of $A \vdash \boldsymbol{M} : \tau\ [\boldsymbol{W}]$. It is not the case, however. The proof fails for the static application, because we cannot prove

$$\mathcal{I}_1 [\![(\mathcal{P}_1 [\![\boldsymbol{W_1}]\!] \rho)\,(\mathcal{P}_1 [\![\boldsymbol{W_2}]\!] \rho)]\!] \rho_{id} \sim_n (\mathcal{I}_1 [\![\boldsymbol{M_1}]\!] \rho')\,(\mathcal{I}_1 [\![\boldsymbol{M_2}]\!] \rho')$$

from the two induction hypotheses

$$\mathcal{I}_1 [\![\mathcal{P}_1 [\![\boldsymbol{W_1}]\!] \rho]\!] \rho_{id} \sim_n \mathcal{I}_1 [\![\boldsymbol{M_1}]\!] \rho'$$

and

$$\mathcal{I}_1 [\![\mathcal{P}_1 [\![\boldsymbol{W_2}]\!] \rho]\!] \rho_{id} \sim_n \mathcal{I}_1 [\![\boldsymbol{M_2}]\!] \rho' \ .$$

Recall the definition of $\mathcal{I}_1$. We have

$$(\mathcal{I}_1 [\![\mathcal{P}_1 [\![\boldsymbol{W_1}]\!] \rho]\!] \rho_{id})\,(\mathcal{I}_1 [\![\mathcal{P}_1 [\![\boldsymbol{W_2}]\!] \rho]\!] \rho_{id}) \quad \sim_n \quad \mathcal{I}_1 [\![(\mathcal{P}_1 [\![\boldsymbol{W_1}]\!] \rho)\underline{@}(\mathcal{P}_1 [\![\boldsymbol{W_2}]\!] \rho)]\!] \rho_{id}$$

but not

$$(\mathcal{I}_1 [\![\mathcal{P}_1 [\![\boldsymbol{W_1}]\!] \rho]\!] \rho_{id})\,(\mathcal{I}_1 [\![\mathcal{P}_1 [\![\boldsymbol{W_2}]\!] \rho]\!] \rho_{id}) \quad \sim_n \quad \mathcal{I}_1 [\![(\mathcal{P}_1 [\![\boldsymbol{W_1}]\!] \rho)\,(\mathcal{P}_1 [\![\boldsymbol{W_2}]\!] \rho)]\!] \rho_{id} \ .$$

Without properly characterizing the behavior of the higher-order function $\mathcal{P}_1 [\![\boldsymbol{W_1}]\!] \rho$, we cannot prove any statement about $(\mathcal{P}_1 [\![\boldsymbol{W_1}]\!] \rho)\,(\mathcal{P}_1 [\![\boldsymbol{W_2}]\!] \rho)$.

If both $\mathcal{P}_1$ and $\mathcal{I}_1$ used a closure rather than a higher-order function as a representation of an abstraction, we might have been able to prove the correctness by induction on the number of evaluation steps. However, this method would make the proof significantly more complicated. We also need to establish the relationship between higher-order functions and closures (in other words, the correctness of defunctionalization). Moreover, it discourages us to use higher-order functions even though we all know how they behave and how useful they are. Rather than transforming our implementation back to the old style, we should go forward and find a method to directly reason about the new style.

## 4. Logical Relations for Call-by-value $\lambda$-calculus

Although the specializer shown in the previous section is correct in the call-by-name semantics, it is not correct in the call-by-value semantics. For example, $(\overline{\boldsymbol{\lambda x.}}\,\underline{\boldsymbol{\lambda y.}}\,\boldsymbol{y})\overline{@}\,\boldsymbol{W}$ will be specialized to $\boldsymbol{\lambda y.\, y}$ even if $\boldsymbol{W}$ is a non-terminating term, such as $(\underline{\boldsymbol{\lambda x.}}\,\boldsymbol{x}\,\underline{@}\,\boldsymbol{x})\underline{@}(\underline{\boldsymbol{\lambda x.}}\,\boldsymbol{x}\,\underline{@}\,\boldsymbol{x})$ which is well-annotated. To see exactly why the correctness proof fails, we try to prove the theorem in the call-by-value semantics. We first define logical relations for the call-by-value $\lambda$-calculus:

$$\begin{array}{lcl} (M, M') \in R_d & \iff & \mathcal{I}_1 [\![M]\!] \rho_{id} \sim_v M' \\ (M, M') \in R_{\sigma\to\tau} & \iff & \forall (V, V') \in R_\sigma.\ (M\,V, M'\,V') \in R_\tau \end{array}$$

There are two differences from the logical relations in the previous section. First, call-by-value equality $\sim_v$ is used instead of call-by-name equality $\sim_n$ in the definition of $R_d$. Secondly, $M$ and $M'$ are allowed to be in $R_{\sigma\to\tau}$ if they transform only related *values* (rather than arbitrary terms) into related terms.

If we could prove Theorem 1 with this definition of $R_\tau$, we would have obtained as a corollary the correctness of the specializer in the call-by-value semantics. However, the proof fails for static applications. Although we could proceed the proof as the same way as the one in the previous section, we would get stuck at the last step where we used the definition of $R_{\sigma\to\tau}$. We need to show that both $\mathcal{P}_1\,[\![\boldsymbol{W_2}]\!]\,\rho$ and $\mathcal{I}_1\,[\![\boldsymbol{M_2}]\!]\,\rho'$ are values, but they are in fact not values if $\boldsymbol{M_2}$ had a form $\boldsymbol{M_{21}} \mathbin{@} \boldsymbol{M_{22}}$.

## 5. Specializer in CPS

The correctness under the call-by-value semantics does not hold for the specializer in Section 3 because it may discard a non-terminating computation. The standard method to recover the correctness is to perform *let-insertion* [4]. Since let-insertion requires explicit manipulation of continuations, we first rewrite our specializer into CPS as follows:

$$\begin{array}{rcl}
\mathcal{P}_2\,[\![\boldsymbol{x}]\!]\,\rho\,\kappa & = & \kappa\,(\rho\,(\boldsymbol{x})) \\
\mathcal{P}_2\,[\![\overline{\boldsymbol{\lambda}}\boldsymbol{x}\boldsymbol{.}\,\boldsymbol{W}]\!]\,\rho\,\kappa & = & \kappa\,(\lambda x.\,\lambda k.\,\mathcal{P}_2\,[\![\boldsymbol{W}]\!]\,\rho[x/\boldsymbol{x}]\,k) \\
\mathcal{P}_2\,[\![\underline{\boldsymbol{\lambda}}\boldsymbol{x}\boldsymbol{.}\,\boldsymbol{W}]\!]\,\rho\,\kappa & = & \kappa\,(\boldsymbol{\lambda x^\diamond .}\,\mathcal{P}_2\,[\![\boldsymbol{W}]\!]\,\rho[\boldsymbol{x^\diamond}/\boldsymbol{x}]\,\lambda x.\,x) \\
\mathcal{P}_2\,[\![\boldsymbol{W_1} \mathbin{\overline{@}} \boldsymbol{W_2}]\!]\,\rho\,\kappa & = & \mathcal{P}_2\,[\![\boldsymbol{W_1}]\!]\,\rho\,\lambda m.\,\mathcal{P}_2\,[\![\boldsymbol{W_2}]\!]\,\rho\,\lambda n.\,m\,n\,\kappa \\
\mathcal{P}_2\,[\![\boldsymbol{W_1} \mathbin{\underline{@}} \boldsymbol{W_2}]\!]\,\rho\,\kappa & = & \mathcal{P}_2\,[\![\boldsymbol{W_1}]\!]\,\rho\,\lambda m.\,\mathcal{P}_2\,[\![\boldsymbol{W_2}]\!]\,\rho\,\lambda n.\,\kappa\,(m \mathbin{@} n)
\end{array}$$

Note that $\boldsymbol{\lambda x^\diamond .}\,\cdots$ and $m \mathbin{@} n$ in the dynamic rules are not CPS-transformed because they are merely data representing baselanguage terms. If we transformed them into CPS, we would obtain the result of specialization in CPS, as we did in the previous work [3].

We then replace the last rule with the following:

$$\mathcal{P}_2\,[\![\boldsymbol{W_1} \mathbin{\underline{@}} \boldsymbol{W_2}]\!]\,\rho\,\kappa \;=\; \mathcal{P}_2\,[\![\boldsymbol{W_1}]\!]\,\rho\,\lambda m.\,\mathcal{P}_2\,[\![\boldsymbol{W_2}]\!]\,\rho\,\lambda n.\,\textbf{let}\ \boldsymbol{t^\diamond} = m \mathbin{@} n\ \textbf{in}\ \kappa\,(\boldsymbol{t^\diamond})$$

where $\textbf{let}\ \boldsymbol{t} = \boldsymbol{M_1}\ \textbf{in}\ \boldsymbol{M_2}$ is an abbreviation for $(\boldsymbol{\lambda t.}\,\boldsymbol{M_2}) \mathbin{@} \boldsymbol{M_1}$. Whenever an application is residualized, we insert a let expression to residualize it exactly once with a unique name $\boldsymbol{t^\diamond}$, and continue the rest of the specialization with this name. Since the residualized application is not passed to the continuation $\kappa$, it will never be discarded even if $\kappa$ discards its argument.

The let-insertion technique can be regarded as performing A-normalization [11] on the fly during specialization. If we extract the rules for variables, dynamic abstractions, and dynamic applications from $\mathcal{P}_2$, we obtain the following one-pass A-normalizer written in CPS [11]:

$$\begin{array}{rcl}
\mathcal{A}_1\,[\![\boldsymbol{x}]\!]\,\rho\,\kappa & = & \kappa\,(\rho\,(\boldsymbol{x})) \\
\mathcal{A}_1\,[\![\boldsymbol{\lambda x.}\,\boldsymbol{M}]\!]\,\rho\,\kappa & = & \kappa\,(\boldsymbol{\lambda x^\diamond .}\,\mathcal{A}_1\,[\![\boldsymbol{M}]\!]\,\rho[\boldsymbol{x^\diamond}/\boldsymbol{x}]\,\lambda x.\,x) \\
\mathcal{A}_1\,[\![\boldsymbol{M_1} \mathbin{@} \boldsymbol{M_2}]\!]\,\rho\,\kappa & = & \mathcal{A}_1\,[\![\boldsymbol{M_1}]\!]\,\rho\,\lambda m.\,\mathcal{A}_1\,[\![\boldsymbol{M_2}]\!]\,\rho\,\lambda n.\,\textbf{let}\ \boldsymbol{t^\diamond} = m \mathbin{@} n\ \textbf{in}\ \kappa\,(\boldsymbol{t^\diamond})
\end{array}$$

We now want to show the correctness of the specializer $\mathcal{P}_2$ under the call-by-value semantics. Namely, we want to show:

$$\mathcal{I}_1\,[\![\mathcal{P}_2\,[\![\boldsymbol{W}]\!]\,\rho_\phi\,\lambda x.\,x]\!]\,\rho_{id} \sim_v \mathcal{I}_1\,[\![\boldsymbol{M}]\!]\,\rho_\phi$$

along the similar story as we did in Section 3. Since the direct proof would get stuck for static applications, we use logical relations. Let us define the base case $R_d$ as follows:

$$(M, M') \in R_d \iff \mathcal{I}_1\,[\![M]\!]\,\rho_{id} \sim_v M' \ .$$

Then, we want to show

$$(\mathcal{P}_2\,[\![\boldsymbol{W}]\!]\,\rho_\phi\,\lambda x.\,x, \mathcal{I}_1\,[\![\boldsymbol{M}]\!]\,\rho_\phi) \in R_d$$

with a suitable definition of $R_{\sigma\to\tau}$.

To prove it, we first generalize the statement to make induction work. Rather than proving only the case where environments and continuations are the empty ones, we prove something like:

$$(\mathcal{P}_2\,[\![\boldsymbol{W}]\!]\,\rho\,\lambda v.\,K, (\lambda v'.\,K')\,(\mathcal{I}_1\,[\![\boldsymbol{M}]\!]\,\rho')) \in R_\tau$$

for some suitable $\rho$, $\rho'$, $\lambda v.\,K$, and $\lambda v'.\,K'$. Since $\mathcal{I}_1$ is written in direct style, we introduce its continuation as a form of a direct application.

Now, how can we define $R_{\sigma\to\tau}$? Unlike Section 3, it is not immediately clear how to define $R_{\sigma\to\tau}$. Obviously, we can not use the previous definition:

$$(M, M') \in R_{\sigma\to\tau} \iff \forall (V, V') \in R_\sigma.\ (M\,V, M'\,V') \in R_\tau$$

because the specializer is written in CPS. Even though $\boldsymbol{W}$ has a type $\sigma \to \tau$, $\mathcal{P}_2\,[\![\boldsymbol{W}]\!]\,\rho\,\lambda v.\,K$ is not a function from $\sigma$ to $\tau$, so we cannot pass it a value of type $\sigma$. Instead, a function of type $\sigma \to \tau$ is consumed by the continuation $\lambda v.\,K$, and $\mathcal{P}_2\,[\![\boldsymbol{W}]\!]\,\rho\,\lambda v.\,K$ produces the final result which can be of any type.

To relate $\mathcal{P}_2\,[\![\boldsymbol{W}]\!]\,\rho\,\lambda v.\,K$ and $(\lambda v'.\,K')\,(\mathcal{I}_1\,[\![\boldsymbol{M}]\!]\,\rho')$ properly, we need to characterize precisely the two continuations, $\lambda v.\,K$ and $\lambda v'.\,K'$, and the final results. Going back to the definition of $\mathcal{P}_2$, we notice two things:

- $\mathcal{P}_2\,[\![\boldsymbol{W}]\!]\,\rho\,\lambda v.\,K$ as a whole returns a dynamic expression.
- $\lambda v.\,K$ returns a dynamic expression, given some value $v$.

They are particularly evident in the rule for dynamic applications:

$$\mathcal{P}_2\,[\![\boldsymbol{M_1} \mathbin{@} \boldsymbol{M_2}]\!]\,\rho\,\kappa \;=\; \mathcal{P}_2\,[\![\boldsymbol{M_1}]\!]\,\rho\,\lambda m.\,\mathcal{P}_2\,[\![\boldsymbol{M_2}]\!]\,\rho\,\lambda n.\,\textbf{let}\ \boldsymbol{t}^\diamond = m \mathbin{@} n\ \textbf{in}\ \kappa\,(\boldsymbol{t}^\diamond)$$

We assumed here that $\kappa$ returns a dynamic expression, which is then used to construct a let-expression (and hence, $\mathcal{P}_2$ also returns a dynamic expression). In ordinary CPS programs, the return type of continuations is polymorphic. It can be of any type, usually referred to as a type *Answer*. Here, we used $\kappa$ in a non-standard way, however. We instantiated the *Answer* type into a type of dynamic expressions and used the result of the application to $\kappa$ to construct a let-expression.

Taking into account that the type of dynamic expressions is $d$, the above observation leads us to the following definition of logical relations:

$$\begin{array}{ll}(M, M') \in R_d & \iff \mathcal{I}_1\,[\![M]\!]\,\rho_{id} \sim_v M' \\ (M, M') \in R_{\sigma\to\tau} & \iff \forall (V, V') \in R_\sigma.\ \forall (\lambda v.\,K, \lambda v'.\,K') \models \tau \rightsquigarrow d.\ (M\,V\,\lambda v.\,K, (\lambda v'.\,K')\,(M'\,V')) \in R_d\end{array}$$

where $(\lambda v.\,K, \lambda v'.\,K') \models \tau \rightsquigarrow d$ is simultaneously defined as follows:

$$(\lambda v.\,K, \lambda v'.\,K') \models \tau \rightsquigarrow d \iff \forall (V, V') \in R_\tau.\ ((\lambda v.\,K)\,V, (\lambda v'.\,K')\,V') \in R_d$$

Intuitively, $(\lambda v.\,K, \lambda v'.\,K') \models \tau \rightsquigarrow d$ means that $\lambda v.\,K$ and $\lambda v'.\,K'$ are related continuations that, given related values of type $\tau$, produce related results of type $d$. Using this definition, $(M, M') \in R_{\sigma\to\tau}$ states that $M$ and $M'$ are related if they produce related results of type $d$, given related values of type $\tau$ and related continuations of type $\tau \rightsquigarrow d$. In the following, we use $\rightsquigarrow$ for the type of continuations.

With this definition of logical relations, we can prove the correctness of $\mathcal{P}_2$ under the call-by-value semantics.

THEOREM 2. *If* $A \vdash \boldsymbol{M} : \tau\ [\boldsymbol{W}]$, $(\rho, \rho') \models A$, *and* $(\lambda v.\,K, \lambda v'.\,K') \models \tau \rightsquigarrow d$, *then* $(\mathcal{P}_2\,[\![\boldsymbol{W}]\!]\,\rho\,\lambda v.\,K, (\lambda v'.\,K')\,(\mathcal{I}_1\,[\![\boldsymbol{M}]\!]\,\rho')) \in R_d$.

The proof of this theorem is by induction on the structure of the proof of $A \vdash \boldsymbol{M} : \tau\ [\boldsymbol{W}]$. Even though $\mathcal{P}_2$ is written in CPS, the induction does work thanks to the explicit reference to the types of continuations and

the final result. The proof proceeds in a CPS manner. In particular, the cases for (both static and dynamic) applications go from left to right. We use the induction hypotheses for the function part and the argument part in this order.

By instantiating the theorem to the case where both the environment and the continuation are empty, we obtain the following corollary that establishes the correctness of a specializer using the continuation-based let-insertion:

COROLLARY 2. *If* $\vdash \boldsymbol{M} : d\,[\boldsymbol{W}]$, *then* $\mathcal{I}_1\,[\![\mathcal{P}_2\,[\![\boldsymbol{W}]\!]\,\rho_\phi\,\lambda x.\,x]\!]\,\rho_{id} \sim_v \mathcal{I}_1\,[\![\boldsymbol{M}]\!]\,\rho_\phi$.

If we annotate the input to the specializer completely dynamic, the specializer behaves exactly the same as the A-normalizer. Thus, the theorem can be instantiated to the following corollary, which proves the correctness of the continuation-based A-normalization.

COROLLARY 3. $\mathcal{I}_1\,[\![\mathcal{A}_1\,[\![\boldsymbol{M}]\!]\,\rho_\phi\,\lambda x.\,x]\!]\,\rho_{id} \sim_v \mathcal{I}_1\,[\![\boldsymbol{M}]\!]\,\rho_\phi$.

## 6. Specializer in Direct Style

In this section, we present a specializer written in direct style and show its correctness under the call-by-value semantics. Since we have already established the correctness of a specializer written in CPS in the previous section, the development in this section is easy. Roughly speaking, we transform the results in the previous section *back to direct style* [5, 9]. During this process, we use the first-class delimited continuation constructs, *shift* and *reset*, to cope with non-standard use of continuations. Here is the definition of the specializer written in direct style:

$$\begin{array}{rcl}
\mathcal{P}_3\,[\![\boldsymbol{x}]\!]\,\rho & = & \rho\,(\boldsymbol{x}) \\
\mathcal{P}_3\,[\![\overline{\boldsymbol{\lambda}}\boldsymbol{x}.\,\boldsymbol{W}]\!]\,\rho & = & \lambda x.\,\mathcal{P}_3\,[\![\boldsymbol{W}]\!]\,\rho[x/\boldsymbol{x}] \\
\mathcal{P}_3\,[\![\underline{\boldsymbol{\lambda}}\boldsymbol{x}.\,\boldsymbol{W}]\!]\,\rho & = & \boldsymbol{\lambda x^\diamond}.\,\langle \mathcal{P}_3\,[\![\boldsymbol{W}]\!]\,\rho[\boldsymbol{x}^\diamond/\boldsymbol{x}]\rangle \\
\mathcal{P}_3\,[\![\boldsymbol{W_1}\,\overline{@}\,\boldsymbol{W_2}]\!]\,\rho & = & (\mathcal{P}_3\,[\![\boldsymbol{W_1}]\!]\,\rho)\,(\mathcal{P}_3\,[\![\boldsymbol{W_2}]\!]\,\rho) \\
\mathcal{P}_3\,[\![\boldsymbol{W_1}\,\underline{@}\,\boldsymbol{W_2}]\!]\,\rho & = & \xi\kappa.\,\mathbf{let}\ \boldsymbol{t}^\diamond = (\mathcal{P}_3\,[\![\boldsymbol{W_1}]\!]\,\rho)@(\mathcal{P}_3\,[\![\boldsymbol{W_2}]\!]\,\rho)\ \mathbf{in}\ \kappa\,(\boldsymbol{t}^\diamond)
\end{array}$$

As in the previous section, we obtain the one-pass A-normalizer written in direct style with shift and reset [3] by extracting dynamic rules from $\mathcal{P}_3$:

$$\begin{array}{rcl}
\mathcal{A}_2\,[\![\boldsymbol{x}]\!]\,\rho & = & \rho\,(\boldsymbol{x}) \\
\mathcal{A}_2\,[\![\boldsymbol{\lambda x}.\,\boldsymbol{M}]\!]\,\rho & = & \boldsymbol{\lambda x^\diamond}.\,\langle \mathcal{A}_2\,[\![\boldsymbol{M}]\!]\,\rho[\boldsymbol{x}^\diamond/\boldsymbol{x}]\rangle \\
\mathcal{A}_2\,[\![\boldsymbol{M_1}\,@\,\boldsymbol{M_2}]\!]\,\rho & = & \xi\kappa.\,\mathbf{let}\ \boldsymbol{t}^\diamond = (\mathcal{A}_2\,[\![\boldsymbol{M_1}]\!]\,\rho)@(\mathcal{A}_2\,[\![\boldsymbol{M_2}]\!]\,\rho)\ \mathbf{in}\ \kappa\,(\boldsymbol{t}^\diamond)
\end{array}$$

To define suitable logical relations for the specializer written in direct style (with shift and reset), we need to correctly handle delimited continuations. The key insight is to make the exact correspondence between continuations in the previous section and delimited continuations in this section. In particular, we type the result of the delimited continuations as $d$.

Logical relations for the direct-style specializer with delimited continuations are defined as follows:

$$\begin{array}{lcl}
(M, M') \in \boldsymbol{R}_d & \iff & \mathcal{I}_1\,[\![M]\!]\,\rho_{id} \sim_v M' \\
(M, M') \in \boldsymbol{R}_{\sigma\to\tau} & \iff & \forall (V, V') \in \boldsymbol{R}_\sigma.\,\forall (\lambda v.\,K, \lambda v'.\,K') \models \tau \rightsquigarrow d. \\
 & & (\langle (\lambda v.\,K)\,(M\,V)\rangle, (\lambda v'.\,K')\,(M'\,V')) \in \boldsymbol{R}_d
\end{array}$$

where $(\lambda v.\,K, \lambda v'.\,K') \models \tau \rightsquigarrow d$ is simultaneously defined as follows:

$$(\lambda v.\,K, \lambda v'.\,K') \models \tau \rightsquigarrow d \iff \forall (V, V') \in \boldsymbol{R}_\tau.\,(\langle (\lambda v.\,K)\,V\rangle, (\lambda v'.\,K')\,V') \in \boldsymbol{R}_d$$

Then, the correctness of the specializer is stated as follows:

THEOREM 3. *If* $A \vdash \boldsymbol{M} : \tau\,[\boldsymbol{W}]$, $(\rho, \rho') \models A$, *and* $(\lambda v.\,K, \lambda v'.\,K') \models \tau \rightsquigarrow d$, *then* $(\langle (\lambda v.\,K)\,(\mathcal{P}_3\,[\![\boldsymbol{W}]\!]\,\rho)\rangle, (\lambda v'.\,K')\,(\mathcal{I}_1\,[\![\boldsymbol{M}]\!]\,\rho')) \in \boldsymbol{R}_d$.

Although both the specializer and the interpreter are written in direct style, the proof proceeds in a CPS manner. In particular, the cases for applications go from left to right, naturally reflecting the call-by-value semantics.

By instantiating the theorem to the case where both the environment and the continuation are empty, we obtain the following corollary that establishes the correctness of a specializer using the shift/reset-based let-insertion:

COROLLARY 4. *If* $\vdash \boldsymbol{M} : d\,[\boldsymbol{W}]$, *then* $\mathcal{I}_1\,[\![\langle \mathcal{P}_3\,[\![\boldsymbol{W}]\!]\,\rho_\phi\rangle]\!]\,\rho_{id} \sim_v \mathcal{I}_1\,[\![\boldsymbol{M}]\!]\,\rho_\phi$.

As before, if we annotate the input to the specializer completely dynamic, the specializer behaves exactly the same as the A-normalizer. Thus, the theorem can be instantiated to the following corollary, which proves the correctness of the direct-style A-normalization.

COROLLARY 5. $\mathcal{I}_1\,[\![\langle \mathcal{A}_2\,[\![\boldsymbol{M}]\!]\,\rho_\phi\rangle]\!]\,\rho_{id} \sim_v \mathcal{I}_1\,[\![\boldsymbol{M}]\!]\,\rho_\phi$.

## 7. Interpreter and A-normalizer for Shift and Reset

So far, shift and reset appeared only in the metalanguage. In the following sections, we develop a specializer written in direct style that can handle the call-by-value $\lambda$-calculus with shift and reset in the baselanguage. We first define an interpreter, a residualizer, and an A-normalizer for the call-by-value $\lambda$-calculus with shift and reset. We then try to combine the interpreter and the A-normalizer to obtain a specializer in the next section.

Here is the interpreter written in direct style:

$$\begin{array}{rcl}
\mathcal{I}_2\,[\![\boldsymbol{x}]\!]\,\rho & = & \rho\,(\boldsymbol{x}) \\
\mathcal{I}_2\,[\![\boldsymbol{\lambda x.\,M}]\!]\,\rho & = & \lambda x.\mathcal{I}_2\,[\![\boldsymbol{M}]\!]\,\rho[x/\boldsymbol{x}] \\
\mathcal{I}_2\,[\![\boldsymbol{M_1}\ \boldsymbol{@}\ \boldsymbol{M_2}]\!]\,\rho & = & (\mathcal{I}_2\,[\![\boldsymbol{M_1}]\!]\,\rho)\,(\mathcal{I}_2\,[\![\boldsymbol{M_2}]\!]\,\rho) \\
\mathcal{I}_2\,[\![\boldsymbol{\xi k.\,M}]\!]\,\rho & = & \xi k.\mathcal{I}_2\,[\![\boldsymbol{M}]\!]\,\rho[k/\boldsymbol{k}] \\
\mathcal{I}_2\,[\![\boldsymbol{\langle M\rangle}]\!]\,\rho & = & \langle \mathcal{I}_2\,[\![\boldsymbol{M}]\!]\,\rho\rangle
\end{array}$$

We used shift and reset operations themselves to interpret shift and reset expressions.

A residualizer is defined as follows:

$$\begin{array}{rcl}
\mathcal{D}_2\,[\![\boldsymbol{x}]\!]\,\rho & = & \rho\,(\boldsymbol{x}) \\
\mathcal{D}_2\,[\![\boldsymbol{\lambda x.\,M}]\!]\,\rho & = & \boldsymbol{\lambda x^\diamond.}\,\mathcal{D}_2\,[\![\boldsymbol{M}]\!]\,\rho[\boldsymbol{x^\diamond}/\boldsymbol{x}] \\
\mathcal{D}_2\,[\![\boldsymbol{M_1}\ \boldsymbol{@}\ \boldsymbol{M_2}]\!]\,\rho & = & (\mathcal{D}_2\,[\![\boldsymbol{M_1}]\!]\,\rho)\boldsymbol{@}(\mathcal{D}_2\,[\![\boldsymbol{M_2}]\!]\,\rho) \\
\mathcal{D}_2\,[\![\boldsymbol{\xi k.\,M}]\!]\,\rho & = & \boldsymbol{\xi k^\diamond.}\,\mathcal{D}_2\,[\![\boldsymbol{M}]\!]\,\rho[\boldsymbol{k^\diamond}/\boldsymbol{k}] \\
\mathcal{D}_2\,[\![\boldsymbol{\langle M\rangle}]\!]\,\rho & = & \boldsymbol{\langle}\mathcal{D}_2\,[\![\boldsymbol{M}]\!]\,\rho\boldsymbol{\rangle}
\end{array}$$

It simply renames bound variables and keeps other expressions unchanged. As before, this residualizer is not suitable for specializers. We instead use the following A-normalizer:

$$\begin{array}{rcl}
\mathcal{A}_3\,[\![\boldsymbol{x}]\!]\,\rho & = & \rho\,(\boldsymbol{x}) \\
\mathcal{A}_3\,[\![\boldsymbol{\lambda x.\,M}]\!]\,\rho & = & \boldsymbol{\lambda x^\diamond.}\,\langle \mathcal{A}_3\,[\![\boldsymbol{M}]\!]\,\rho[\boldsymbol{x^\diamond}/\boldsymbol{x}]\rangle \\
\mathcal{A}_3\,[\![\boldsymbol{M_1}\ \boldsymbol{@}\ \boldsymbol{M_2}]\!]\,\rho & = & \xi k.\,\textbf{let}\ \boldsymbol{t^\diamond} = (\mathcal{A}_3\,[\![\boldsymbol{M_1}]\!]\,\rho)\boldsymbol{@}(\mathcal{A}_3\,[\![\boldsymbol{M_2}]\!]\,\rho)\ \textbf{in}\ k\,(\boldsymbol{t^\diamond}) \\
\mathcal{A}_3\,[\![\boldsymbol{\xi k.\,M}]\!]\,\rho & = & \boldsymbol{\xi k^\diamond.}\,\langle \mathcal{A}_3\,[\![\boldsymbol{M}]\!]\,\rho[\boldsymbol{k^\diamond}/\boldsymbol{k}]\rangle \\
\mathcal{A}_3\,[\![\boldsymbol{\langle M\rangle}]\!]\,\rho & = & \boldsymbol{\langle}\langle \mathcal{A}_3\,[\![\boldsymbol{M}]\!]\,\rho\rangle\boldsymbol{\rangle}
\end{array}$$

It replaces all the application expressions in the body of abstractions, shift expressions, and reset operations with a sequence of let-expressions.

## 8. Specializer for Shift and Reset

In this section, we show a specializer for the call-by-value $\lambda$-calculus with shift and reset. Our first attempt is to combine the interpreter and the A-normalizer as we did before for the calculi without shift and reset:

$$
\begin{array}{rcl}
\mathcal{P}_4\,[\![\boldsymbol{x}]\!]\,\rho & = & \rho\,(\boldsymbol{x}) \\
\mathcal{P}_4\,[\![\overline{\boldsymbol{\lambda}}\boldsymbol{x}\boldsymbol{.}\,\boldsymbol{W}]\!]\,\rho & = & \lambda x.\,\mathcal{P}_4\,[\![\boldsymbol{W}]\!]\,\rho[x/\boldsymbol{x}] \\
\mathcal{P}_4\,[\![\underline{\boldsymbol{\lambda}}\boldsymbol{x}\boldsymbol{.}\,\boldsymbol{W}]\!]\,\rho & = & \boldsymbol{\lambda}\boldsymbol{x}^{\diamond}\boldsymbol{.}\,\langle\mathcal{P}_4\,[\![\boldsymbol{W}]\!]\,\rho[\boldsymbol{x}^{\diamond}/\boldsymbol{x}]\rangle \\
\mathcal{P}_4\,[\![\boldsymbol{W_1}\,\overline{@}\,\boldsymbol{W_2}]\!]\,\rho & = & (\mathcal{P}_4\,[\![\boldsymbol{W_1}]\!]\,\rho)\,(\mathcal{P}_4\,[\![\boldsymbol{W_2}]\!]\,\rho) \\
\mathcal{P}_4\,[\![\boldsymbol{W_1}\,\underline{@}\,\boldsymbol{W_2}]\!]\,\rho & = & \xi k.\,\textbf{let}\ \boldsymbol{t}^{\diamond} = (\mathcal{P}_4\,[\![\boldsymbol{W_1}]\!]\,\rho)@(\mathcal{P}_4\,[\![\boldsymbol{W_2}]\!]\,\rho)\ \textbf{in}\ k\,(\boldsymbol{t}^{\diamond}) \\
\mathcal{P}_4\,[\![\overline{\boldsymbol{\xi}}\boldsymbol{k}\boldsymbol{.}\,\boldsymbol{W}]\!]\,\rho & = & \xi k.\,\mathcal{P}_4\,[\![\boldsymbol{W}]\!]\,\rho[k/\boldsymbol{k}] \\
\mathcal{P}_4\,[\![\underline{\boldsymbol{\xi}}\boldsymbol{k}\boldsymbol{.}\,\boldsymbol{W}]\!]\,\rho & = & \boldsymbol{\xi}\boldsymbol{k}^{\diamond}\boldsymbol{.}\,\langle\mathcal{P}_4\,[\![\boldsymbol{W}]\!]\,\rho[\boldsymbol{k}^{\diamond}/\boldsymbol{k}]\rangle \\
\mathcal{P}_4\,[\![\overline{\boldsymbol{\langle}\boldsymbol{W}\boldsymbol{\rangle}}]\!]\,\rho & = & \langle\mathcal{P}_4\,[\![\boldsymbol{W}]\!]\,\rho\rangle \\
\mathcal{P}_4\,[\![\underline{\boldsymbol{\langle}\boldsymbol{W}\boldsymbol{\rangle}}]\!]\,\rho & = & \boldsymbol{\langle}\langle\mathcal{P}_4\,[\![\boldsymbol{W}]\!]\,\rho\rangle\boldsymbol{\rangle}
\end{array}
$$

Although this specializer does seem to work for carefully annotated inputs, it is hard to specify the well-annotated term as a simple binding-time analysis. The difficulty comes from the inconsistency between the specialization-time continuation and the runtime continuation.

In the rule for the static shift, a continuation is grabbed at specialization time, which means that we implicitly assume the grabbed continuation coincides with the actual continuation at runtime. This was actually true for the interpreter: we implemented shift in the baselanguage using shift in the metalanguage. In the specializer, however, the specialization-time continuation does not always coincide with the actual continuation. To be more specific, in the rule for dynamic abstractions, we specialize the body $\boldsymbol{W}$ in a static reset (*i.e.*, in the empty continuation) to perform A-normalization, but the actual continuation at the time when $\boldsymbol{W}$ is executed is not necessarily the empty one. Rather, it is the one when the abstraction is applied at runtime. For example, consider the term $\underline{\boldsymbol{\lambda}}\boldsymbol{x}\boldsymbol{.}\,\boldsymbol{f}\,\underline{@}\,\overline{\boldsymbol{\xi}}\boldsymbol{k}\boldsymbol{.}\,\cdots$. The above specializer incorrectly captures the continuation $\boldsymbol{f}\,\underline{@}\,\cdot$ as $\boldsymbol{k}$, but actually $\boldsymbol{k}$ should be bound to $\boldsymbol{h}\,\underline{@}(\boldsymbol{f}\,\underline{@}\,\cdot)$ where $\boldsymbol{h}$ is the continuation at the time when $\underline{\boldsymbol{\lambda}}\boldsymbol{x}\boldsymbol{.}\,\boldsymbol{f}\,\underline{@}\,\overline{\boldsymbol{\xi}}\boldsymbol{k}\boldsymbol{.}\,\cdots$ is applied to an argument.

Given that the specialization-time continuation is not always consistent with the actual one, we have to make sure that the continuation is captured statically only when it represents the actual one. Furthermore, we have to make sure that whenever shift is residualized, its enclosing reset is also residualized. One way to express this information in the type system would be to split all the typing rules into two, one for the case when the specialization-time continuation and the actual continuation coincide (or, the continuation is known, static) and the other for the case when they do not (the continuation is unknown, dynamic). We could then statically grab the continuation only when it represents the actual one.

However, this solution leads to an extremely weak specialization. Unless an enclosing reset is known at specialization time, we cannot grab continuations statically. Thus, under dynamic abstractions, no shift operation is possible at specialization time. Furthermore, because we use a type-based binding-time analysis, it becomes impossible to perform *any* specialization under dynamic abstractions. Remember that a type system does not tell us what subexpressions appear in a given expression, but only the type of the given expression. From a type system, we cannot distinguish the expression that does not contain any shift expressions from the one that does. Thus, even if $\boldsymbol{W_1}$ turns out to have a static function type in $\boldsymbol{W_1}\,@\,\boldsymbol{W_2}$ (and thus it appears that this application can be performed statically), we cannot actually perform this application, because the toplevel operator of $\boldsymbol{W_1}$ might be a shift operation that passes a function to the grabbed continuation. In other words, we cannot determine the binding-time of $\boldsymbol{W_1}\,@\,\boldsymbol{W_2}$ from the binding-time of $\boldsymbol{W_1}$, which makes it difficult to construct a simple type-based binding-time analysis.

The solution we employ takes a different approach. We maintain the consistency between specialization-time continuations and actual ones *all the time*. In other words, we make the continuation always static. The modified

specializer is presented as follows:

$$\begin{array}{rcl}
\mathcal{P}_5\,[\![\boldsymbol{x}]\!]\,\rho & = & \rho\,(\boldsymbol{x}) \\
\mathcal{P}_5\,[\![\overline{\boldsymbol{\lambda}}\boldsymbol{x}.\,\boldsymbol{W}]\!]\,\rho & = & \lambda x.\,\mathcal{P}_5\,[\![\boldsymbol{W}]\!]\,\rho[x/\boldsymbol{x}] \\
\mathcal{P}_5\,[\![\underline{\boldsymbol{\lambda}}\boldsymbol{x}.\,\boldsymbol{W}]\!]\,\rho & = & \boldsymbol{\lambda x^{\diamond}.\,\xi k^{\diamond}.\,\langle\langle k^{\diamond}\,@(\mathcal{P}_5\,[\![W]\!]\,\rho[x^{\diamond}/x])\rangle\rangle} \\
\mathcal{P}_5\,[\![\boldsymbol{W_1}\,\overline{@}\,\boldsymbol{W_2}]\!]\,\rho & = & (\mathcal{P}_5\,[\![\boldsymbol{W_1}]\!]\,\rho)\,(\mathcal{P}_5\,[\![\boldsymbol{W_2}]\!]\,\rho) \\
\mathcal{P}_5\,[\![\boldsymbol{W_1}\,\underline{@}\,\boldsymbol{W_2}]\!]\,\rho & = & \xi k.\,\textbf{let}\ t^{\diamond} = (\mathcal{P}_5\,[\![\boldsymbol{W_1}]\!]\,\rho)@(\mathcal{P}_5\,[\![\boldsymbol{W_2}]\!]\,\rho)\ \textbf{in}\ k\,(t^{\diamond}) \\
\mathcal{P}_5\,[\![\overline{\boldsymbol{\xi}}\boldsymbol{k}.\,\boldsymbol{W}]\!]\,\rho & = & \xi k.\,\mathcal{P}_5\,[\![\boldsymbol{W}]\!]\,\rho[k/\boldsymbol{k}] \\
\mathcal{P}_5\,[\![\underline{\boldsymbol{\xi}}\boldsymbol{k}.\,\boldsymbol{W}]\!]\,\rho & = & \xi k.\,\mathcal{P}_5\,[\![\boldsymbol{W}]\!]\,\rho[\boldsymbol{\lambda v^{\diamond}.\,\langle k\,v^{\diamond}\rangle}/\boldsymbol{k}] \\
\mathcal{P}_5\,[\![\overline{\langle\boldsymbol{W}\rangle}]\!]\,\rho & = & \langle\mathcal{P}_5\,[\![\boldsymbol{W}]\!]\,\rho\rangle
\end{array}$$

There are three changes from $\mathcal{P}_4$. The first and the most important change is in the rule for dynamic abstractions. Rather than specializing the body $\boldsymbol{W}$ of a dynamic abstraction in the empty context, we specialize it in the context $\langle\boldsymbol{k}^{\diamond}\,@\,\cdot\,\rangle$. This specialization-time continuation $\langle\boldsymbol{k}^{\diamond}\,@\,\cdot\,\rangle$ turns out to be consistent with the runtime continuation, because the variable $\boldsymbol{k}^{\diamond}$ is bound in the dynamic shift placed directly under the dynamic abstraction and represents the continuation when the abstraction is applied at runtime.

Another way to understand the rule for dynamic abstractions is by rewriting the rule for static abstractions as follows:

$$\mathcal{P}_5\,[\![\overline{\boldsymbol{\lambda}}\boldsymbol{x}.\,\boldsymbol{W}]\!]\,\rho \quad = \quad \lambda x.\,\xi k.\,\langle k\,(\mathcal{P}_5\,[\![\boldsymbol{W}]\!]\,\rho[x/\boldsymbol{x}])\rangle$$

In this equivalent definition, the continuation $k$ for the body of the static abstraction is made explicit by inserting a shift operation. Comparing this rule to the rule for dynamic abstractions, we can easily see the correspondence between them. In the rule for dynamic abstractions, the body $\boldsymbol{W}$ is specialized in the yet unknown context $\langle\boldsymbol{k}^{\diamond}\,@\,\cdot\,\rangle$ that corresponds to the correct context $\langle k\,(\cdot)\rangle$.

This insertion of a dynamic shift is reminiscent of $\eta$-expansion. To remove administrative redexes in the one-pass CPS transformation, Danvy and Filinski [8] turned all the continuations that are unknown at transformation time into static functions using $\eta$-expansion. The above insertion of the dynamic shift does exactly the same thing in the direct-style program.

The second change is in the rule for dynamic shift. Rather than residualizing a dynamic shift, which requires residualization of the corresponding reset, the current continuation is grabbed and it is turned into a dynamic expression via $\eta$-expansion. Finally, the rule for dynamic reset is removed since all the shift operations are taken care of during specialization time, and there is no need to residualize reset. (This does not necessarily mean that the result of specialization does not contain any reset expressions. Reset is residualized in the rule for dynamic abstractions.)

These changes not only define a correct specializer but result in a quite powerful one. It can now handle *partially static continuations*. Consider the term $\underline{\boldsymbol{\lambda}}\boldsymbol{f}.\,\underline{\boldsymbol{\lambda}}\boldsymbol{x}.\,\boldsymbol{f}\,\underline{@}\,\overline{\boldsymbol{\xi}}\boldsymbol{k}.\,\boldsymbol{k}\,\overline{@}(\boldsymbol{k}\,\overline{@}\,\boldsymbol{x})$. (This term is well-annotated in the type system shown in the next section.) When we specialize this term, the continuation $\boldsymbol{k}$ grabbed by $\overline{\boldsymbol{\xi}}\boldsymbol{k}.\,\cdots$ is partially static: we know that the first thing to do when $\boldsymbol{k}$ is applied is to pass its argument to $\boldsymbol{f}$, but the computation that should be performed after that is unknown. It is the continuation when $\underline{\boldsymbol{\lambda}}\boldsymbol{x}.\,\cdots$ is applied to an argument. Even in this case, $\mathcal{P}_5$ can expand this partial continuation into the result of specialization. By naming the unknown continuation $\boldsymbol{h}$, $\mathcal{P}_5$ produces the following output (after removing unnecessary dynamic shift and inlining the residualized let expressions):

$$\boldsymbol{\lambda f.\,\lambda x.\,\xi h.\,\langle h\,@(f\,@\,\langle h\,@(f\,@\,x)\rangle)\rangle}\ .$$

Observe that the partial continuation $\langle\boldsymbol{h}\,@(\boldsymbol{f}\,@\,\cdot)\rangle$ is expanded twice in the result. If $\boldsymbol{f}$ were static, we could have been able to perform further specialization, exploiting the partially static information of the continuation.

On the other hand, the above changes cause an interesting side-effect to the result of specialization: all the residualized lambda abstractions now have a 'standardized' form $\boldsymbol{\lambda x.\,\xi k.}\,\cdots$ (and this is the only place where shift is residualized). In particular, if we specialize $\underline{\boldsymbol{\lambda}}\boldsymbol{x}.\,\boldsymbol{W}$ where shift is not used during the evaluation of $\boldsymbol{W}$,

the residualized abstraction has always the form $\boldsymbol{\lambda x.\, \xi k^{\diamond}.\, \langle k^{\diamond} \mathbin{@} M \rangle}$ or $\boldsymbol{\lambda x.\, \xi k^{\diamond}.\, \mathbf{let}\ t_1 = M_1\ \mathbf{in}\ \cdots \mathbf{let}\ t_n = M_n\ \mathbf{in}\ \langle k^{\diamond} \mathbin{@} t_n \rangle}$ where $k^{\diamond}$ does not occur free in $M$ and $M_i$. If we used $\mathcal{P}_3$ instead, we would have obtained the equivalent but simpler results: $\boldsymbol{\lambda x.\, M}$ or $\boldsymbol{\lambda x.\, \mathbf{let}\ t_1 = M_1\ \mathbf{in}\ \cdots \mathbf{let}\ t_n = M_n\ \mathbf{in}\ t_n}$. In other words, $\mathcal{P}_5$ is not a conservative extension of $\mathcal{P}_3$.

A question then is whether it is possible to obtain the latter results on the fly using $\mathcal{P}_5$ with some extra work. We expect that it is not likely. As long as a simple type-based binding-time analysis is employed, it is impossible to tell if the execution of the body of a dynamic abstraction includes any shift operations. So, unless we introduce some extra mechanisms to keep track of this information, there is no way to avoid the insertion of a dynamic shift in the rule for dynamic abstractions. Then, rather than making the specializer complicated, we would employ a simple post-processing to remove unnecessary shift expressions, if it is important at all to do so. Currently, we are investigating if the standardized occurrence of shift has any effects on the efficient and direct implementation of delimited continuations.

## 9. Type System for Shift and Reset

Since our proof technique relies on the logical relations, we need to define a type system for the call-by-value $\lambda$-calculus with shift and reset to prove the correctness of $\mathcal{P}_5$. In this section, we briefly review Danvy and Filinski's type system [6]. More thorough explanation is found in [3, 6].

In the presence of first-class (delimited) continuations, we need to explicitly specify the types of continuations and the final result. For this purpose, Danvy and Filinski use a judgment of the following form:

$$A, \alpha \vdash \boldsymbol{M} : \tau, \beta\ [\boldsymbol{W}]$$

It reads: under the type assumption $A$, an expression $\boldsymbol{M}$ has a type $\tau$ in a continuation of type $\tau \rightsquigarrow \alpha$ and the final result is of type $\beta$. Since we use this type system as the static part of our binding-time analysis, we decorate it with $[\boldsymbol{W}]$ to indicate that $\boldsymbol{M}$ is annotated as $\boldsymbol{W}$.

If $\boldsymbol{M}$ does not contain any shift operations, the types $\alpha$ and $\beta$ are always the same, namely, the *Answer* type. In the presence of shift and reset, however, they can be different and of any type.

The type of functions also need to include the types of continuations and the final result. It has the form: $\sigma/\alpha \to \tau/\beta$. It is a type of functions that receive an argument of type $\sigma$ and returns a value of type $\tau$ to a continuation of type $\tau \rightsquigarrow \alpha$ and the final result is of type $\beta$. As a result, types are specified as follows:

$$\tau \quad = \quad d \mid \tau/\tau \to \tau/\tau$$

Here goes the type system:

$$A[\boldsymbol{x} : \tau], \alpha \vdash \boldsymbol{x} : \tau, \alpha\ [\boldsymbol{x}]$$

$$\frac{A[\boldsymbol{x} : \sigma], \alpha \vdash \boldsymbol{M} : \tau, \beta\ [\boldsymbol{W}]}{A, \delta \vdash \boldsymbol{\lambda x.\, M} : \sigma/\alpha \to \tau/\beta, \delta\ [\overline{\boldsymbol{\lambda} \boldsymbol{x.\, W}}]}$$

$$\frac{\begin{array}{l} A, \delta \vdash \boldsymbol{M_1} : \sigma/\alpha \to \tau/\epsilon, \beta\ [\boldsymbol{W_1}] \\ A, \epsilon \vdash \boldsymbol{M_2} : \sigma, \delta\ [\boldsymbol{W_2}] \end{array}}{A, \alpha \vdash \boldsymbol{M_1 \mathbin{@} M_2} : \tau, \beta\ [\boldsymbol{W_1} \mathbin{\overline{@}} \boldsymbol{W_2}]}$$

$$\frac{A[\boldsymbol{k} : \tau/\delta \to \alpha/\delta], \sigma \vdash \boldsymbol{M} : \sigma, \beta\ [\boldsymbol{W}]}{A, \alpha \vdash \boldsymbol{\xi k.\, M} : \tau, \beta\ [\overline{\boldsymbol{\xi} \boldsymbol{k.\, W}}]}$$

$$\frac{A, \sigma \vdash \boldsymbol{M} : \sigma, \tau\ [\boldsymbol{W}]}{A, \alpha \vdash \boldsymbol{\langle M \rangle} : \tau, \alpha\ [\overline{\boldsymbol{\langle W \rangle}}]}$$

The above type system is a generalization of the standard type system where types of continuations are made explicit. In Section 6, the result type of continuations and the type of final results were always $d$. In the above type system, it means that a judgment had always the form $A, d \vdash \boldsymbol{M} : \tau, d\ [\boldsymbol{W}]$ and the function type had always the form $\sigma/d \to \tau/d$. So if we write them as $A \vdash \boldsymbol{M} : \tau\ [\boldsymbol{W}]$ and $\sigma \to \tau$, respectively, we obtain exactly the same type system as the one for the ordinary $\lambda$-calculus (the three static rules shown in Section 3).

The dynamic rules can be obtained by simply replacing all the static function types with $d$ (and types that occur within the function type). The dynamic rules are as follows:

$$\frac{A[\boldsymbol{x} : d], d \vdash \boldsymbol{M} : d, d\ [\boldsymbol{W}]}{A, \delta \vdash \boldsymbol{\lambda x.\, M} : d, \delta\ [\underline{\boldsymbol{\lambda}}\boldsymbol{x.\, W}]}$$

$$\frac{A, \delta \vdash \boldsymbol{M_1} : d, \beta\ [\boldsymbol{W_1}] \quad A, d \vdash \boldsymbol{M_2} : d, \delta\ [\boldsymbol{W_2}]}{A, d \vdash \boldsymbol{M_1}\ @\ \boldsymbol{M_2} : d, \beta\ [\boldsymbol{W_1}\ \underline{@}\ \boldsymbol{W_2}]}$$

$$\frac{A[\boldsymbol{k} : d], \sigma \vdash \boldsymbol{M} : \sigma, \beta\ [\boldsymbol{W}]}{A, d \vdash \boldsymbol{\xi k.\, M} : d, \beta\ [\underline{\boldsymbol{\xi}}\boldsymbol{k.\, W}]}$$

## 10. Logical Relations for Shift and Reset

In this section, we define the logical relations for the call-by-value $\lambda$-calculus with shift and reset, which are used to prove the correctness of the specializer $\mathcal{P}_5$ presented in Section 8. They are the generalization of the logical relations in Section 6 in that the type of the final result and the result of continuations are not restricted to $d$.

$$\begin{array}{lcl}
(M, M') \in \boldsymbol{R}_d & \iff & \mathcal{I}_2\,[\![M]\!]\,\rho_{id} \sim_v M' \\
(M, M') \in \boldsymbol{R}_{\sigma/\alpha \to \tau/\beta} & \iff & \forall (V, V') \in \boldsymbol{R}_\sigma.\, \forall (\lambda v.\, K, \lambda v'.\, K') \models \tau \rightsquigarrow \alpha. \\
 & & (\langle (\lambda v.\, K)\,(M\ V) \rangle, \langle (\lambda v'.\, K')\,(M'\ V') \rangle) \in \boldsymbol{R}_\beta
\end{array}$$

where $(\lambda v.\, K, \lambda v'.\, K') \models \tau \rightsquigarrow \alpha$ is simultaneously defined as follows:

$$(\lambda v.\, K, \lambda v'.\, K') \models \tau \rightsquigarrow \alpha \iff \forall (V, V') \in \boldsymbol{R}_\tau.\, (\langle (\lambda v.\, K)\, V \rangle, \langle (\lambda v'.\, K')\, V' \rangle) \in \boldsymbol{R}_\alpha$$

Then, the correctness of the specializer is stated as follows:

THEOREM 4. *If* $A, \alpha \vdash \boldsymbol{M} : \tau, \beta\ [\boldsymbol{W}]$, $(\rho, \rho') \models A$, *and* $(\lambda v.\, K, \lambda v'.\, K') \models \tau \rightsquigarrow \alpha$, *then* $(\langle (\lambda v.\, K)\,(\mathcal{P}_5\,[\![\boldsymbol{W}]\!]\,\rho) \rangle, \langle (\lambda v'.\, K')\,(\mathcal{I}_2\,[\![\boldsymbol{M}]\!]\,\rho') \rangle) \in \boldsymbol{R}_\beta$.

By instantiating the theorem to the case where both the environment and the continuation are empty, we obtain the following corollary that establishes the correctness of a direct-style specializer that can handle shift and reset:

COROLLARY 6. *If* $d \vdash \boldsymbol{M} : d, d\ [\boldsymbol{W}]$, *then* $\mathcal{I}_2\,[\![\langle \mathcal{P}_5\,[\![\boldsymbol{W}]\!]\,\rho_\phi \rangle]\!]\,\rho_{id} \sim_v \langle \mathcal{I}_2\,[\![\boldsymbol{M}]\!]\,\rho_\phi \rangle$.

The complete proof of the theorem is found in Appendix for the interested reviewers.

## 11. Strong Normalization

The basic idea behind the logical relations shown in this paper is not restricted to proving the correctness of specializers. To see how it can be applied to other proofs, we present in this section the proof of strong normalization for the typed call-by-value $\lambda$-calculus with shift and reset. Ariola, Herbelin, and Sabry [1] presented a similar result by embedding shift and reset into their $\lambda_{\mathcal{C}}^{\rightarrow -}$-calculus and then showing that $\lambda_{\mathcal{C}}^{\rightarrow -}$-calculus is strongly normalizing. We give a more direct proof here. Thanks to the natural definition of the logical relations, the proof is a simple exercise, following the standard proof technique found in a textbook [17, Chapter 12].

We first extend the base- and metalanguage with integers:

$$\begin{array}{rcl} \boldsymbol{M} & = & \cdots \mid \boldsymbol{n} \\ M & = & \cdots \mid n \end{array}$$

as well as the interpreter:

$$\mathcal{I}_2 [\![\boldsymbol{n}]\!] \rho \;\; = \;\; n$$

Here, $n$ is the integer in the metalanguage that corresponds to the numeral $\boldsymbol{n}$. Types are defined by:

$$\tau \;\; = \;\; \mathit{int} \mid \tau/\tau \to \tau/\tau$$

Typing rules are given by:

$$A, \alpha \vdash \boldsymbol{n} : \mathit{int}, \alpha$$

together with the five static rules in Section 9 (ignoring the parts for annotated terms "$[\boldsymbol{W}]$"). Now, define the logical relations (or predicates) $N_\tau$ on the metalanguage terms by induction on the structure of types as follows:

$$\begin{array}{lcl} M \in N_{\mathit{int}} & \iff & M \text{ halts} \\ M \in N_{\sigma/\alpha \to \tau/\beta} & \iff & M \text{ halts, and } \forall V \in N_\sigma . \forall \lambda v.\, K \models \tau \rightsquigarrow \alpha . \langle (\lambda v.\, K)\, (M\, V) \rangle \in N_\beta \end{array}$$

where $\lambda v.\, K \models \tau \rightsquigarrow \alpha$ is simultaneously defined as follows:

$$\lambda v.\, K \models \tau \rightsquigarrow \alpha \;\; \iff \;\; \forall V \in N_\tau .\, \langle (\lambda v.\, K)\, V \rangle \in N_\alpha$$

For an environment $\rho$, we define $\rho \models A$ iff for all $\boldsymbol{x} \in \mathit{dom}(A)$, $\rho(\boldsymbol{x}) \in N_{A(\boldsymbol{x})}$. Then, we can show the following theorem:

THEOREM 5. *If* $A, \alpha \vdash \boldsymbol{M} : \tau, \beta$, $\rho \models A$, *and* $\lambda v.\, K \models \tau \rightsquigarrow \alpha$, *then* $\langle (\lambda v.\, K)\, (\mathcal{I}_2 [\![\boldsymbol{M}]\!] \rho) \rangle \in N_\beta$.

We can instantiate this theorem in many ways according to which initial continuation we use, but if we instantiate it to an empty continuation $\lambda v.\, v$ of type $\alpha \rightsquigarrow \alpha$ together with an empty environment, we obtain the following corollary:

COROLLARY 7. *If* $\alpha \vdash \boldsymbol{M} : \alpha, \tau$ *for some* $\alpha$ *and* $\tau$, *then* $\langle \mathcal{I}_2 [\![\boldsymbol{M}]\!] \rho_\phi \rangle$ *halts.*

Namely, if $\boldsymbol{M}$ is typed under an empty environment and an empty continuation, the execution of $\boldsymbol{M}$ in the empty context always terminates.

## 12. Related Work

This work extends our earlier work [3] where we presented offline specializers for $\lambda$-terms with shift and reset that produced the output in CPS. The present work is a direct-style account of the previous work, but it contains non-trivial definition of logical relations for shift and reset. We also presented the *online* specializers for the $\lambda$-calculus with shift and reset [2]. However, their correctness has not been formally proved.

Thiemann [18] presented an offline partial evaluator for Scheme including call/cc. In his partial evaluator, call/cc is reduced if the captured continuation and the body of call/cc are both static. This is close to our first attempt in Section 8. Our solution is more liberal and reduces more continuation-capturing constructs, but with a side-effect that all the residualized abstractions include a toplevel shift, which could be removed by a simple post-processing. More recently, Thiemann [21] showed a sophisticated effect-based type system to show the equivalence of the continuation-based let-insertion and the state-based let-insertion. His type system captures the information on the let-residualized code as an effect. It might be possible to extend his framework to avoid unnecessary shift at the front of dynamic abstractions on the fly.

The correctness proof for offline specializers using the technique of logical relations appears in Jones et al. [13, Chapter 8]. Wand [22] used it to prove the correctness of an offline specializer for the call-by-name $\lambda$-calculus. The present work is a non-trivial extension of his work to cope with delimited continuations. Wand's

formulation was based on substitution, but we used the environment-based formulation, which is essentially the same but is more close to the implementation.

The type system used in this paper is due to Danvy and Filinski [6]. A similar type system is studied by Ariola, Herbelin, and Sabry [1], which explicitly mentions the type of continuations.

## 13. Conclusion

This paper demonstrated that logical relations can be defined to characterize not only call-by-name higher-order functions but also call-by-value functions as well as delimited continuations. They were used to show the correctness of various offline specializers, including the one for the call-by-value $\lambda$-calculus with shift and reset. Along the development, we also established the correctness of the continuation-based let-insertion, the shift/reset-based let-insertion, the continuation-based A-normalization, and the shift/reset-based A-normalization. Finally, the idea of logical relations was used to give a simple and direct proof of the strong normalization for the typed call-by-value $\lambda$-calculus with shift and reset.

## References


[1] Ariola, Z. M., H. Herbelin, and A Sabry "A Type-Theoretic Foundation of Continuations and Prompts," *Proceedings of the ninth ACM SIGPLAN International Conference on Functional Programming (ICFP'04)*, pp. 40–53 (September 2004).

[2] Asai, K. "Online Partial Evaluation for Shift and Reset," *ACM SIGPLAN Workshop on Partial Evaluation and Semantics-Based Program Manipulation (PEPM '02)*, pp. 19–30 (January 2002).

[3] Asai, K. "Offline Partial Evaluation for Shift and Reset," *ACM SIGPLAN Symposium on Partial Evaluation and Semantics-Based Program Manipulation (PEPM '04)*, pp. 3–14 (August 2004).

[4] Bondorf, A., and O. Danvy "Automatic autoprojection of recursive equations with global variables and abstract data types," *Science of Computer Programming*, Vol. 16, pp. 151–195, Elsevier (1991).

[5] Danvy, O. "Back to Direct Style," *Science of Computer Programming*, Vol. 22, pp. 183–195, Elsevier (February 1994).

[6] Danvy, O., and A. Filinski "A Functional Abstraction of Typed Contexts," Technical Report 89/12, DIKU, University of Copenhagen (July 1989).

[7] Danvy, O., and A. Filinski "Abstracting Control," *Proceedings of the 1990 ACM Conference on Lisp and Functional Programming*, pp. 151–160 (June 1990).

[8] Danvy, O., and A. Filinski "Representing Control, a Study of the CPS Transformation," *Mathematical Structures in Computer Science*, Vol. 2, No. 4, pp. 361–391 (December 1992).

[9] Danvy, O., and J. L. Lawall "Back to Direct Style II: First-Class Continuations," *Proceedings of the 1992 ACM Conference on Lisp and Functional Programming*, pp. 299–310 (June 1992).

[10] Filinski, A. "Representing Monads," *Conference Record of the 21st Annual ACM Symposium on Principles of Programming Languages*, pp. 446–457 (January 1994).

[11] Flanagan, C., A. Sabry, B. F. Duba, and M. Felleisen "The Essence of Compiling with Continuations," *Proceedings of the ACM SIGPLAN '93 Conference on Programming Language Design and Implementation (PLDI)*, pp. 237–247 (June 1993).

[12] Gasbichler, M., and M. Sperber "Final Shift for Call/cc: Direct Implementation of Shift and Reset," *Proceedings of the ACM SIGPLAN International Conference on Functional Programming (ICFP'02)*, pp. 271–282 (October 2002).

[13] Jones, N. D., C. K. Gomard, and P. Sestoft *Partial Evaluation and Automatic Program Generation*, New York: Prentice-Hall (1993).

[14] Kameyama, Y., and M. Hasegawa "A Sound and Complete Axiomatization of Delimited Continuations," *Proceedings of the eighth ACM SIGPLAN International Conference on Functional Programming (ICFP'03)*, pp. 177–188 (August 2003).

[15] Lawall, J. L., and O. Danvy "Continuation-Based Partial Evaluation," *Proceedings of the 1994 ACM Conference on Lisp and Functional Programming*, pp. 227–238 (June 1994).

[16] Mitchell, J. C. *Foundations for Programming Languages*, Cambridge: MIT Press (1996).

[17] Pierce, B. C. *Types and Programming Languages*, Cambridge: MIT Press (2002).

[18] Thiemann, P. "Towards Partial Evaluation of Full Scheme," *Proceedings of Reflection'96*, pp. 105–115 (April 1996).

[19] Thiemann, P. J. "Cogen in Six Lines," *Proceedings of the ACM SIGPLAN International Conference on Functional Programming (ICFP'96)*, pp. 180–189 (May 1996).

[20] Thiemann, P. "Combinators for Program Generation," *Journal of Functional Programming*, Vol. 9, No. 5, pp. 483–525, Cambridge University Press (September 1999).

[21] Thiemann, P. "Continuation-Based Partial Evaluation without Continuation," In R. Cousot, editor, *Static Analysis (LNCS 2694)*, pp. 366–382 (June 2003).

[22] Wand, M. "Specifying the Correctness of Binding-Time Analysis," *Journal of Functional Programming*, Vol. 3, No. 3, pp. 365–387, Cambridge University Press (July 1993).

## A. Appendix

For the interested reviewers, the appendix shows the correctness proof for the specializer $\mathcal{P}_5$. In the appendix, we write $\mathcal{P}$ for $\mathcal{P}_5$, $\mathcal{I}$ for $\mathcal{I}_2$ and $\sim$ for $\sim_v$.

## B. Axioms for Shift and Reset

(Pure) evaluation contexts:

$$\begin{array}{rcl} F & = & [\,] \mid F\,M \mid V\,F \mid \xi k.\,F \mid \\ & & \boldsymbol{\lambda x.}\,F \mid F \mathbin{\boldsymbol{@}} M \mid V \mathbin{\boldsymbol{@}} F \mid \boldsymbol{\xi k.}\,F \mid \boldsymbol{\langle} F \boldsymbol{\rangle} \mid \\ & & \overline{\boldsymbol{\lambda} \boldsymbol{x.}}\,F \mid \underline{\boldsymbol{\lambda} \boldsymbol{x.}}\,F \mid F \mathbin{\overline{\boldsymbol{@}}} M \mid V \mathbin{\overline{\boldsymbol{@}}} F \mid F \mathbin{\underline{\boldsymbol{@}}} M \mid V \mathbin{\underline{\boldsymbol{@}}} F \mid \overline{\boldsymbol{\xi} \boldsymbol{k.}}\,F \mid \underline{\boldsymbol{\xi} \boldsymbol{k.}}\,F \mid \overline{\boldsymbol{\langle} F \boldsymbol{\rangle}} \mid \underline{\boldsymbol{\langle} F \boldsymbol{\rangle}} \end{array}$$

Note that static reset is not permitted in this context except for appearing within $M$.

Sound and complete axioms for the call-by-value $\lambda$-calculus with shift and reset presented by Kameyama and Hasegawa [14]:

$$\begin{array}{rcll} (\lambda x.\,M)\,V & \sim & M[V/x] & \beta_v \\ \lambda x.\,V\,x & \sim & V & \text{if } x \notin \mathit{FV}(V) \quad \eta_v \\ (\lambda x.\,\boldsymbol{F}[x])\,M & \sim & \boldsymbol{F}[M] & \text{if } x \notin \mathit{FV}(F) \quad \beta_\Omega \\ \langle V \rangle & \sim & V & \textit{reset-value} \\ \langle (\lambda x.\,M_1)\,\langle M_2 \rangle \rangle & \sim & (\lambda x.\,\langle M_1 \rangle)\,\langle M_2 \rangle & \textit{reset-lift} \\ \xi k.\,k\,M & \sim & M & \text{if } k \notin \mathit{FV}(M) \quad \textit{shift-elim} \\ \langle \boldsymbol{F}[\xi k.\,M] \rangle & \sim & \langle (\lambda k.\,M)\,(\lambda x.\,\langle \boldsymbol{F}[x] \rangle) \rangle & \text{if } x \notin \mathit{FV}(F) \quad \textit{reset-shift} \\ \xi k.\,\langle M \rangle & \sim & \xi k.\,M & \textit{shift-reset} \end{array}$$

We also use the following axiom proved in [14]:

$$\langle \langle M \rangle \rangle \sim \langle M \rangle \quad \textit{reset-reset}$$

## C. Some Propositions

LEMMA 1 (Admissibility, Wand [22]). *If $M_1 \sim M_1'$ and $M_2 \sim M_2'$, then $(M_1, M_2) \in \boldsymbol{R}_\tau \iff (M_1', M_2') \in \boldsymbol{R}_\tau$.*

PROOF. By induction on the length $|\tau|$ of $\tau$, defined by $|d| = 0$ and $|\sigma/\alpha \to \tau/\beta| = |\beta| + 1$. If the type is $d$, then

$$\begin{array}{rcl} (M_1, M_2) \in \boldsymbol{R}_d & \iff & \mathcal{I}_2\,[\![M_1]\!]\,\rho_{id} \sim_v M_2 \\ & \iff & \mathcal{I}_2\,[\![M_1']\!]\,\rho_{id} \sim_v M_2' \\ & \iff & (M_1', M_2') \in \boldsymbol{R}_d \end{array}$$

If the type is $\sigma/\alpha \to \tau/\beta$, then $|\beta| < |\sigma/\alpha \to \tau/\beta|$, so we have

$$\begin{array}{rcl} & & (M_1, M_2) \in \boldsymbol{R}_{\sigma/\alpha \to \tau/\beta} \\ & \iff & \forall (V_1, V_2) \in \boldsymbol{R}_\sigma.\, \forall (\lambda v_1.\,K_1, \lambda v_2.\,K_2) \models \tau \rightsquigarrow \alpha.\, (\langle (\lambda v_1.\,K_1)\,(M_1\,V_1) \rangle, \langle (\lambda v_2.\,K_2)\,(M_2\,V_2) \rangle) \in \boldsymbol{R}_\beta \\ & \iff & \forall (V_1, V_2) \in \boldsymbol{R}_\sigma.\, \forall (\lambda v_1.\,K_1, \lambda v_2.\,K_2) \models \tau \rightsquigarrow \alpha.\, (\langle (\lambda v_1.\,K_1)\,(M_1'\,V_1) \rangle, \langle (\lambda v_2.\,K_2)\,(M_2'\,V_2) \rangle) \in \boldsymbol{R}_\beta \\ & \iff & (M_1', M_2') \in \boldsymbol{R}_{\sigma/\alpha \to \tau/\beta} \end{array}$$

□

PROPOSITION 1. $(\lambda x.\, x, \lambda x.\, x) \models \tau \rightsquigarrow \tau$ *for any* $\tau$.

PROOF. Let $(V, V') \in R_\tau$. We need to show $(\langle(\lambda x.\, x)\, V\rangle, \langle(\lambda x.\, x)\, V'\rangle) \in R_\tau$. Since

$$\langle(\lambda x.\, x)\, V\rangle \quad \sim \quad \langle V\rangle \quad \sim \quad V$$

and the same for $V'$, the statement follows from the Admissibility Lemma. □

PROPOSITION 2. $(\lambda v.\, \langle\!\langle \boldsymbol{k}^\diamond \mathbin{@} v \rangle\!\rangle, \lambda v'.\, k^\diamond\, v') \models d \rightsquigarrow d$.

PROOF. Let $(V, V') \in R_d$. From the definition of $R_d$, we have $\mathcal{I}\,[\![V]\!]\,\rho_{id} \sim V'$. We need to show

$$(\langle(\lambda v.\, \langle\!\langle \boldsymbol{k}^\diamond \mathbin{@} v \rangle\!\rangle)\, V\rangle, \langle(\lambda v'.\, k^\diamond\, v')\, V'\rangle) \in R_d \ .$$

The two terms reduce as follows:

$$\begin{array}{lcl} \langle(\lambda v.\, \langle\!\langle \boldsymbol{k}^\diamond \mathbin{@} v \rangle\!\rangle)\, V\rangle & \sim & \langle \langle\!\langle \boldsymbol{k}^\diamond \mathbin{@} V \rangle\!\rangle \rangle \quad \sim \quad \langle\!\langle \boldsymbol{k}^\diamond \mathbin{@} V \rangle\!\rangle \\ \langle(\lambda v'.\, k^\diamond\, v')\, V'\rangle & \sim & \langle k^\diamond\, V'\rangle \end{array}$$

From the Admissibility Lemma, we now need to show

$$(\langle\!\langle \boldsymbol{k}^\diamond \mathbin{@} V \rangle\!\rangle, \langle k^\diamond\, V'\rangle) \in R_d \ .$$

We calculate:

$$\begin{array}{lcl} \mathcal{I}\,[\![\langle\!\langle \boldsymbol{k}^\diamond \mathbin{@} V \rangle\!\rangle]\!]\,\rho_{id} & \sim & \langle \mathcal{I}\,[\![\boldsymbol{k}^\diamond \mathbin{@} V]\!]\,\rho_{id}\rangle \\ & \sim & \langle(\mathcal{I}\,[\![\boldsymbol{k}^\diamond]\!]\,\rho_{id})\,(\mathcal{I}\,[\![V]\!]\,\rho_{id})\rangle \\ & \sim & \langle k^\diamond\, V'\rangle \end{array}$$

□

## D. Correctness

THEOREM 4. *If* $A, \alpha \vdash \boldsymbol{M} : \tau, \beta\ [\boldsymbol{W}]$, $(\rho, \rho') \models A$, *and* $(\lambda v.\, K, \lambda v'.\, K') \models \tau \rightsquigarrow \alpha$, *then* $(\langle(\lambda v.\, K)\,(\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho)\rangle, \langle(\lambda v'.\, K')\,(\mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho')\rangle) \in R_\beta$.

PROOF. By induction on the structure of the proof of $A, \alpha \vdash \boldsymbol{M} : \tau, \beta\ [\boldsymbol{W}]$.

***Case 1 (Variable).*** Assume $\boldsymbol{x} \in dom(A)$. Then $A[\boldsymbol{x} : \tau], \alpha \vdash \boldsymbol{x} : \tau, \alpha\ [\boldsymbol{x}]$. We need to show

$$(\langle(\lambda v.\, K)\,(\mathcal{P}\,[\![\boldsymbol{x}]\!]\,\rho)\rangle, \langle(\lambda v'.\, K')\,(\mathcal{I}\,[\![\boldsymbol{x}]\!]\,\rho')\rangle) \in R_\alpha$$

assuming $(\rho, \rho') \models A[\boldsymbol{x} : \tau]$ and $(\lambda v.\, K, \lambda v'.\, K') \models \tau \rightsquigarrow \alpha$. From the definition of $\mathcal{P}$ and $\mathcal{I}$ and the Admissibility Lemma, we have:

$$\begin{array}{cl} & (\langle(\lambda v.\, K)\,(\mathcal{P}\,[\![\boldsymbol{x}]\!]\,\rho)\rangle, \langle(\lambda v'.\, K')\,(\mathcal{I}\,[\![\boldsymbol{x}]\!]\,\rho')\rangle) \in R_\alpha \\ \iff & (\langle(\lambda v.\, K)\,(\rho\,(\boldsymbol{x}))\rangle, \langle(\lambda v'.\, K')\,(\rho'\,(\boldsymbol{x}))\rangle) \in R_\alpha \end{array}$$

which holds because $(\rho, \rho') \models A$ and $(\lambda v.\, K, \lambda v'.\, K') \models \tau \rightsquigarrow \alpha$.

***Case 2 (Static Abstraction).*** Assume

$$\frac{A[\boldsymbol{x}:\sigma], \alpha \vdash \boldsymbol{M} : \tau, \beta\ [\boldsymbol{W}]}{A, \delta \vdash \boldsymbol{\lambda x.\, M} : \sigma/\alpha \to \tau/\beta, \delta\ [\overline{\boldsymbol{\lambda}}\boldsymbol{x.\, W}]}$$

We need to show

$$(\langle(\lambda v.\, K)\,(\mathcal{P}\,[\![\overline{\boldsymbol{\lambda}}\boldsymbol{x.\, W}]\!]\,\rho)\rangle, \langle(\lambda v'.\, K')\,(\mathcal{I}\,[\![\boldsymbol{\lambda x.\, M}]\!]\,\rho')\rangle) \in R_\delta$$

assuming $(\rho, \rho') \models A$ and $(\lambda v.\, K, \lambda v'.\, K') \models (\sigma/\alpha \to \tau/\beta) \rightsquigarrow \delta$. From the definition of $\mathcal{P}$ and $\mathcal{I}$, we have:

$$\begin{array}{ll} & (\langle(\lambda v.\, K)\,(\mathcal{P}\,[\![\overline{\boldsymbol{\lambda}}\boldsymbol{x.\, W}]\!]\,\rho)\rangle, \langle(\lambda v'.\, K')\,(\mathcal{I}\,[\![\boldsymbol{\lambda x.\, M}]\!]\,\rho')\rangle) \in R_\delta \\ \iff & (\langle(\lambda v.\, K)\,(\lambda x.\,\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho[x/\boldsymbol{x}])\rangle, \langle(\lambda v'.\, K')\,(\lambda x.\,\mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho'[x/\boldsymbol{x}])\rangle) \in R_\delta\ . \end{array}$$

Since $(\lambda v.\, K, \lambda v'.\, K') \models (\sigma/\alpha \to \tau/\beta) \rightsquigarrow \delta$, it suffices to show that

$$(\lambda x.\,\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho[x/\boldsymbol{x}], \lambda x.\,\mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho'[x/\boldsymbol{x}]) \in R_{\sigma/\alpha\to\tau/\beta}\ .$$

So assume that $(V, V') \in R_\sigma$ and $(\lambda v.\, L, \lambda v'.\, L') \models \tau \rightsquigarrow \alpha$. We want to show

$$(\langle(\lambda v.\, L)\,((\lambda x.\,\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho[x/\boldsymbol{x}])\,V)\rangle, \langle(\lambda v'.\, L')\,((\lambda x.\,\mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho'[x/\boldsymbol{x}])\,V')\rangle) \in R_\beta$$

which $\beta$-reduces to

$$(\langle(\lambda v.\, L)\,(\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho[V/\boldsymbol{x}])\rangle, \langle(\lambda v'.\, L')\,(\mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho'[V'/\boldsymbol{x}])\rangle) \in R_\beta\ .$$

This statement holds by the induction hypothesis, because $(\rho[V/\boldsymbol{x}], \rho'[V'/\boldsymbol{x}]) \models A[\boldsymbol{x}:\sigma]$ and $(\lambda v.\, L, \lambda v.\, L') \models \tau \rightsquigarrow \alpha$.

***Case 3 (Dynamic Abstraction).*** Assume

$$\frac{A[\boldsymbol{x}:d], d \vdash \boldsymbol{M} : d, d\ [\boldsymbol{W}]}{A, \delta \vdash \boldsymbol{\lambda x.\, M} : d, \delta\ [\underline{\boldsymbol{\lambda}}\boldsymbol{x.\, W}]}$$

We need to show

$$(\langle(\lambda v.\, K)\,(\mathcal{P}\,[\![\underline{\boldsymbol{\lambda}}\boldsymbol{x.\, W}]\!]\,\rho)\rangle, \langle(\lambda v'.\, K')\,(\mathcal{I}\,[\![\boldsymbol{\lambda x.\, M}]\!]\,\rho')\rangle) \in R_\delta$$

assuming $(\rho, \rho') \models A$ and $(\lambda v.\, K, \lambda v'.\, K') \models d \rightsquigarrow \delta$. From the definition of $\mathcal{P}$ and $\mathcal{I}$, we have:

$$\begin{array}{ll} & (\langle(\lambda v.\, K)\,(\mathcal{P}\,[\![\underline{\boldsymbol{\lambda}}\boldsymbol{x.\, W}]\!]\,\rho)\rangle, \langle(\lambda v'.\, K')\,(\mathcal{I}\,[\![\boldsymbol{\lambda x.\, M}]\!]\,\rho')\rangle) \in R_\delta \\ \iff & (\langle(\lambda v.\, K)\,(\boldsymbol{\lambda x^\diamond.\, \xi k^\diamond.}\,\langle\boldsymbol{\langle k^\diamond\,@(\mathcal{P}\,[\![W]\!]\,\rho[x^\diamond/\boldsymbol{x}])\rangle}\rangle)\rangle, \langle(\lambda v'.\, K')\,(\lambda x^\diamond.\,\mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho'[x^\diamond/\boldsymbol{x}])\rangle) \in R_\delta \end{array}$$

Since $(\lambda v.\, K, \lambda v'.\, K') \models d \rightsquigarrow \delta$, it suffices to show that

$$(\boldsymbol{\lambda x^\diamond.\, \xi k^\diamond.}\,\langle\boldsymbol{\langle k^\diamond\,@(\mathcal{P}\,[\![W]\!]\,\rho[x^\diamond/\boldsymbol{x}])\rangle}\rangle, \lambda x^\diamond.\,\mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho'[x^\diamond/\boldsymbol{x}]) \in R_d\ .$$

Now, $(\boldsymbol{x}^\diamond, x^\diamond) \in R_d$ holds, so let $\rho_1 = \rho[\boldsymbol{x}^\diamond/\boldsymbol{x}]$ and $\rho'_1 = \rho'[x^\diamond/\boldsymbol{x}]$; then $(\rho_1, \rho'_1) \models A[\boldsymbol{x}:d]$. Furthermore, let $K_1 = \boldsymbol{\langle k^\diamond\,@\,v\rangle}$ and $K'_1 = k^\diamond\,v'$; then we have $(\lambda v.\, K_1, \lambda v'.\, K'_1) \models d \rightsquigarrow d$ from Proposition 2. Therefore, by the induction hypothesis, we know that

$$(\langle(\lambda v.\, K_1)\,(\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho_1)\rangle, \langle(\lambda v'.\, K'_1)\,(\mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho'_1)\rangle) \in R_d$$

that is,

$$\mathcal{I}\,[\![\langle(\lambda v.\, K_1)\,(\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho_1)\rangle]\!]\,\rho_{id} \sim \langle(\lambda v'.\, K'_1)\,(\mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho'_1)\rangle \tag{1}$$

Now, to establish

$$(\boldsymbol{\lambda x^\diamond.\, \xi k^\diamond.\, \langle \langle k^\diamond \mathbin{@} (\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho[\boldsymbol{x^\diamond}/\boldsymbol{x}]) \rangle\!\rangle}, \lambda x^\diamond.\, \mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho'[x^\diamond/\boldsymbol{x}]) \in R_d$$

we calculate:

$$\begin{array}{lll}
& \mathcal{I}\,[\![\boldsymbol{\lambda x^\diamond.\, \xi k^\diamond.\, \langle \langle k^\diamond \mathbin{@} (\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho[\boldsymbol{x^\diamond}/\boldsymbol{x}]) \rangle\!\rangle}]\!]\,\rho_{id} & \\
= & \lambda x^\diamond.\, \mathcal{I}\,[\![\boldsymbol{\xi k^\diamond.\, \langle \langle k^\diamond \mathbin{@} (\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho[\boldsymbol{x^\diamond}/\boldsymbol{x}]) \rangle\!\rangle}]\!]\,\rho_{id}[x^\diamond/\boldsymbol{x^\diamond}] & \text{definition of } \mathcal{I} \\
= & \lambda x^\diamond.\, \xi k^\diamond.\, \mathcal{I}\,[\![\langle \langle k^\diamond \mathbin{@} (\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho[\boldsymbol{x^\diamond}/\boldsymbol{x}]) \rangle\!\rangle]\!]\,\rho_{id}[x^\diamond/\boldsymbol{x^\diamond}, k^\diamond/\boldsymbol{k^\diamond}] & \text{definition of } \mathcal{I} \\
= & \lambda x^\diamond.\, \xi k^\diamond.\, \mathcal{I}\,[\![\langle \langle k^\diamond \mathbin{@} (\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho_1) \rangle\!\rangle]\!]\,\rho_{id} & \text{definition of } \rho_1 \text{ and } \rho_{id} \\
\sim & \lambda x^\diamond.\, \xi k^\diamond.\, \mathcal{I}\,[\![\langle (\lambda v.\, \langle \langle k^\diamond \mathbin{@} v \rangle\!\rangle)\, (\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho_1) \rangle]\!]\,\rho_{id} & \beta_\Omega \\
= & \lambda x^\diamond.\, \xi k^\diamond.\, \mathcal{I}\,[\![\langle (\lambda v.\, K_1)\, (\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho_1) \rangle]\!]\,\rho_{id} & \text{definition of } K_1 \\
\sim & \lambda x^\diamond.\, \xi k^\diamond.\, \langle (\lambda v'.\, K_1')\, (\mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho_1') \rangle & \text{Equation (1)} \\
= & \lambda x^\diamond.\, \xi k^\diamond.\, \langle (\lambda v'.\, k^\diamond\, v')\, (\mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho'[x^\diamond/\boldsymbol{x}]) \rangle & \text{definition of } \rho_1' \text{ and } K_1' \\
\sim & \lambda x^\diamond.\, \xi k^\diamond.\, \langle k^\diamond\, (\mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho'[x^\diamond/\boldsymbol{x}]) \rangle & \eta_v \\
\sim & \lambda x^\diamond.\, \xi k^\diamond.\, k^\diamond\, (\mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho'[x^\diamond/\boldsymbol{x}]) & \textit{shift-reset} \\
\sim & \lambda x^\diamond.\, \mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho'[x^\diamond/\boldsymbol{x}] & \textit{shift-elim}
\end{array}$$

***Case 4 (Static Application).*** Assume

$$\frac{\begin{array}{l} A, \delta \vdash \boldsymbol{M_1} : \sigma/\alpha \to \tau/\epsilon, \beta\ [\boldsymbol{W_1}] \\ A, \epsilon \vdash \boldsymbol{M_2} : \sigma, \delta\ [\boldsymbol{W_2}] \end{array}}{A, \alpha \vdash \boldsymbol{M_1 \mathbin{@} M_2} : \tau, \beta\ [\boldsymbol{W_1 \mathbin{\overline{@}} W_2}]}$$

We must show

$$(\langle (\lambda v.\, K)\, (\mathcal{P}\,[\![\boldsymbol{W_1 \mathbin{\overline{@}} W_2}]\!]\,\rho) \rangle, \langle (\lambda v'.\, K')\, (\mathcal{I}\,[\![\boldsymbol{M_1 \mathbin{@} M_2}]\!]\,\rho') \rangle) \in R_\beta$$

assuming $(\rho, \rho') \models A$ and $(\lambda v.\, K, \lambda v'.\, K') \models \tau \rightsquigarrow \alpha$. From the definition of $\mathcal{P}$ and $\mathcal{I}$, we have:

$$\begin{array}{ll}
& (\langle (\lambda v.\, K)\, (\mathcal{P}\,[\![\boldsymbol{W_1 \mathbin{\overline{@}} W_2}]\!]\,\rho) \rangle, \langle (\lambda v'.\, K')\, (\mathcal{I}\,[\![\boldsymbol{M_1 \mathbin{@} M_2}]\!]\,\rho') \rangle) \in R_\beta \\
\iff & (\langle (\lambda v.\, K)\, ((\mathcal{P}\,[\![\boldsymbol{W_1}]\!]\,\rho)\, (\mathcal{P}\,[\![\boldsymbol{W_2}]\!]\,\rho)) \rangle, \langle (\lambda v'.\, K')\, ((\mathcal{I}\,[\![\boldsymbol{M_1}]\!]\,\rho')\, (\mathcal{I}\,[\![\boldsymbol{M_2}]\!]\,\rho')) \rangle) \in R_\beta
\end{array}$$

which can be rewritten using $\beta_\Omega$ to:

$$(\langle (\lambda w_1.\, (\lambda v.\, K)\, (w_1\, (\mathcal{P}\,[\![\boldsymbol{W_2}]\!]\,\rho)))\, (\mathcal{P}\,[\![\boldsymbol{W_1}]\!]\,\rho) \rangle, \langle (\lambda m_1.\, (\lambda v'.\, K')\, (m_1\, (\mathcal{I}\,[\![\boldsymbol{M_2}]\!]\,\rho')))\, (\mathcal{I}\,[\![\boldsymbol{M_1}]\!]\,\rho') \rangle) \in R_\beta$$

Since $(\rho, \rho') \models A$, we are done by the induction hypothesis if we can prove

$$(\lambda w_1.\, (\lambda v.\, K)\, (w_1\, (\mathcal{P}\,[\![\boldsymbol{W_2}]\!]\,\rho)), \lambda m_1.\, (\lambda v'.\, K')\, (m_1\, (\mathcal{I}\,[\![\boldsymbol{M_2}]\!]\,\rho'))) \models (\sigma/\alpha \to \tau/\epsilon) \rightsquigarrow \delta\ .$$

So take any values $(w_1', m_1') \in R_{\sigma/\alpha \to \tau/\epsilon}$. We then need to show

$$(\langle (\lambda v.\, K)\, (w_1'\, (\mathcal{P}\,[\![\boldsymbol{W_2}]\!]\,\rho)) \rangle, \langle (\lambda v'.\, K')\, (m_1'\, (\mathcal{I}\,[\![\boldsymbol{M_2}]\!]\,\rho')) \rangle) \in R_\delta$$

which can be rewritten using $\beta_\Omega$ to:

$$(\langle (\lambda w_2.\, (\lambda v.\, K)\, (w_1'\, w_2))\, (\mathcal{P}\,[\![\boldsymbol{W_2}]\!]\,\rho) \rangle, \langle (\lambda m_2.\, (\lambda v'.\, K')\, (m_1'\, m_2))\, (\mathcal{I}\,[\![\boldsymbol{M_2}]\!]\,\rho') \rangle) \in R_\delta$$

Since $(\rho, \rho') \models A$, we are again done by the induction hypothesis if we can prove

$$(\lambda w_2.\, (\lambda v.\, K)\, (w_1'\, w_2), \lambda m_2.\, (\lambda v'.\, K')\, (m_1'\, m_2)) \models \sigma \rightsquigarrow \epsilon\ .$$

So take any values $(w_2', m_2') \in R_\sigma$. We then need to show

$$(\langle (\lambda v.\, K)\, (w_1'\, w_2') \rangle, \langle (\lambda v'.\, K')\, (m_1'\, m_2') \rangle) \in R_\epsilon$$

which holds because $(\lambda v.\, K, \lambda v'.\, K') \models \tau \rightsquigarrow \alpha$.

***Case 5 (Dynamic Application).*** Assume

$$\frac{A, \delta \vdash \boldsymbol{M_1} : d, \beta\ [\boldsymbol{W_1}] \quad A, d \vdash \boldsymbol{M_2} : d, \delta\ [\boldsymbol{W_2}]}{A, d \vdash \boldsymbol{M_1} \mathbin{@} \boldsymbol{M_2} : d, \beta\ [\boldsymbol{W_1} \mathbin{\underline{@}} \boldsymbol{W_2}]}$$

We need to show

$$(\langle \lambda v.\, K \rangle \mathcal{P}\, [\![ \boldsymbol{W_1} \mathbin{\underline{@}} \boldsymbol{W_2} ]\!]\, \rho, \langle \lambda v'.\, K' \rangle \mathcal{I}\, [\![ \boldsymbol{M_1} \mathbin{@} \boldsymbol{M_2} ]\!]\, \rho') \in R_\beta$$

assuming $(\rho, \rho') \models A$ and $(\lambda v.\, K, \lambda v'.\, K') \models d \rightsquigarrow d$. Because we have:

$$\begin{array}{rcl} \langle (\lambda v.\, K)\, (\mathcal{P}\, [\![ \boldsymbol{W_1} \mathbin{\underline{@}} \boldsymbol{W_2} ]\!]\, \rho) \rangle & = & \langle (\lambda v.\, K)\, (\xi k.\, \textbf{let } \boldsymbol{t^\diamond} = (\mathcal{P}\, [\![ \boldsymbol{W_1} ]\!]\, \rho) \mathbin{@} (\mathcal{P}\, [\![ \boldsymbol{W_2} ]\!]\, \rho) \textbf{ in } k\, (\boldsymbol{t^\diamond})) \rangle \\ & \sim & \langle \textbf{let } \boldsymbol{t^\diamond} = (\mathcal{P}\, [\![ \boldsymbol{W_1} ]\!]\, \rho) \mathbin{@} (\mathcal{P}\, [\![ \boldsymbol{W_2} ]\!]\, \rho) \textbf{ in } (\lambda x.\, \langle (\lambda v.\, K)\, x \rangle)\, \boldsymbol{t^\diamond} \rangle \\ & \sim & \langle (\lambda w_1.\, \textbf{let } \boldsymbol{t^\diamond} = w_1 \mathbin{@} (\mathcal{P}\, [\![ \boldsymbol{W_2} ]\!]\, \rho) \textbf{ in } (\lambda x.\, \langle (\lambda v.\, K)\, x \rangle)\, \boldsymbol{t^\diamond}) (\mathcal{P}\, [\![ \boldsymbol{W_1} ]\!]\, \rho) \rangle \end{array}$$

and

$$\begin{array}{rcl} \langle (\lambda v'.\, K')\, (\mathcal{I}\, [\![ \boldsymbol{M_1} \mathbin{@} \boldsymbol{M_2} ]\!]\, \rho') \rangle & = & \langle (\lambda v'.\, K')\, ((\mathcal{I}\, [\![ \boldsymbol{M_1} ]\!]\, \rho')\, (\mathcal{I}\, [\![ \boldsymbol{M_2} ]\!]\, \rho')) \rangle \\ & \sim & \langle (\lambda m_1.\, (\lambda v'.\, K')\, (m_1\, (\mathcal{I}\, [\![ \boldsymbol{M_2} ]\!]\, \rho')))\, (\mathcal{I}\, [\![ \boldsymbol{M_1} ]\!]\, \rho') \rangle \end{array}$$

we need to show

$$\begin{array}{l} (\langle (\lambda w_1.\, \textbf{let } \boldsymbol{t^\diamond} = w_1 \mathbin{@} (\mathcal{P}\, [\![ \boldsymbol{W_2} ]\!]\, \rho) \textbf{ in } (\lambda x.\, \langle (\lambda v.\, K)\, x \rangle)\, \boldsymbol{t^\diamond}) (\mathcal{P}\, [\![ \boldsymbol{W_1} ]\!]\, \rho) \rangle, \\ \langle (\lambda m_1.\, (\lambda v'.\, K')\, (m_1\, (\mathcal{I}\, [\![ \boldsymbol{M_2} ]\!]\, \rho')))\, (\mathcal{I}\, [\![ \boldsymbol{M_1} ]\!]\, \rho') \rangle) \in R_\beta \end{array}$$

Since $(\rho, \rho') \models A$, we are done by the induction hypothesis if we can prove

$$(\lambda w_1.\, \textbf{let } \boldsymbol{t^\diamond} = w_1 \mathbin{@} (\mathcal{P}\, [\![ \boldsymbol{W_2} ]\!]\, \rho) \textbf{ in } (\lambda x.\, \langle (\lambda v.\, K)\, x \rangle)\, \boldsymbol{t^\diamond}, \lambda m_1.\, (\lambda v'.\, K')\, (m_1\, (\mathcal{I}\, [\![ \boldsymbol{M_2} ]\!]\, \rho'))) \models d \rightsquigarrow \delta \ .$$

So take any values $(w_1', m_1') \in R_d$. We then need to show

$$(\, \textbf{let } \boldsymbol{t^\diamond} = w_1' \mathbin{@} (\mathcal{P}\, [\![ \boldsymbol{W_2} ]\!]\, \rho) \textbf{ in } (\lambda x.\, \langle (\lambda v.\, K)\, x \rangle)\, \boldsymbol{t^\diamond}, \langle (\lambda v'.\, K')\, (m_1'\, (\mathcal{I}\, [\![ \boldsymbol{M_2} ]\!]\, \rho')) \rangle) \in R_\delta$$

which can be rewritten using $\beta_\Omega$ to:

$$(\langle (\lambda w_2.\, \textbf{let } \boldsymbol{t^\diamond} = w_1' \mathbin{@} w_2 \textbf{ in } (\lambda x.\, \langle (\lambda v.\, K)\, x \rangle)\, \boldsymbol{t^\diamond}) (\mathcal{P}\, [\![ \boldsymbol{W_2} ]\!]\, \rho) \rangle, \langle (\lambda m_2.\, (\lambda v'.\, K')\, (m_1'\, m_2))\, (\mathcal{I}\, [\![ \boldsymbol{M_2} ]\!]\, \rho') \rangle) \in R_\delta$$

Since $(\rho, \rho') \models A$, we are again done by the induction hypothesis if we can prove

$$(\lambda w_2.\, \textbf{let } \boldsymbol{t^\diamond} = w_1' \mathbin{@} w_2 \textbf{ in } (\lambda x.\, \langle (\lambda v.\, K)\, x \rangle)\, \boldsymbol{t^\diamond}, \lambda m_2.\, (\lambda v'.\, K')\, (m_1'\, m_2)) \models d \rightsquigarrow d \ .$$

So take any values $(w_2', m_2') \in R_d$. We then need to show

$$(\langle \textbf{let } \boldsymbol{t^\diamond} = w_1' \mathbin{@} w_2' \textbf{ in } (\lambda x.\, \langle (\lambda v.\, K)\, x \rangle)\, \boldsymbol{t^\diamond} \rangle, \langle (\lambda v'.\, K')\, (m_1'\, m_2') \rangle) \in R_d$$

which can be reduced to:

$$(\langle \textbf{let } \boldsymbol{t^\diamond} = w_1' \mathbin{@} w_2' \textbf{ in } \langle (\lambda v.\, K)\, \boldsymbol{t^\diamond} \rangle \rangle, \langle (\lambda v'.\, K')\, (m_1'\, m_2') \rangle) \in R_d$$

and then to (using $\beta_v$ (for let), *reset-reset*, and $\beta_v$):

$$(\, \textbf{let } \boldsymbol{t^\diamond} = w_1' \mathbin{@} w_2' \textbf{ in } \langle (\lambda v.\, K)\, \boldsymbol{t^\diamond} \rangle, \langle (\lambda v'.\, K')\, (m_1'\, m_2') \rangle) \in R_d \ .$$

We calculate:

$$\begin{array}{rcll} & \mathcal{I}\, [\![ \textbf{let } \boldsymbol{t^\diamond} = w_1' \mathbin{@} w_2' \textbf{ in } \langle (\lambda v.\, K)\, \boldsymbol{t^\diamond} \rangle ]\!]\, \rho_{id} & & \\ = & \text{let } t^\diamond = \mathcal{I}\, [\![ w_1' \mathbin{@} w_2' ]\!]\, \rho_{id} \text{ in } \mathcal{I}\, [\![ \langle (\lambda v.\, K)\, \boldsymbol{t^\diamond} \rangle ]\!]\, \rho_{id}[t^\diamond / \boldsymbol{t^\diamond}] & & \text{definition of } \mathcal{I} \\ = & \text{let } t^\diamond = (\mathcal{I}\, [\![ w_1' ]\!]\, \rho_{id})\, (\mathcal{I}\, [\![ w_2' ]\!]\, \rho_{id}) \text{ in } \mathcal{I}\, [\![ \langle (\lambda v.\, K)\, \boldsymbol{t^\diamond} \rangle ]\!]\, \rho_{id} & & \text{definition of } \mathcal{I} \text{ and } \rho_{id} \\ \sim & \text{let } t^\diamond = m_1'\, (\mathcal{I}\, [\![ w_2' ]\!]\, \rho_{id}) \text{ in } \mathcal{I}\, [\![ \langle (\lambda v.\, K)\, \boldsymbol{t^\diamond} \rangle ]\!]\, \rho_{id} & & (w_1', m_1') \in R_d \\ \sim & \text{let } t^\diamond = m_1'\, m_2' \text{ in } \mathcal{I}\, [\![ \langle (\lambda v.\, K)\, \boldsymbol{t^\diamond} \rangle ]\!]\, \rho_{id} & & (w_2', m_2') \in R_d \\ \sim & \text{let } t^\diamond = m_1'\, m_2' \text{ in } \langle (\lambda v'.\, K')\, t^\diamond \rangle & & (\lambda v.\, K, \lambda v'.\, K') \models d \rightsquigarrow d \text{ and } (\boldsymbol{t^\diamond}, t^\diamond) \in R_d \\ \sim & \langle (\lambda v'.\, K')\, m_1'\, m_2' \rangle & & \beta_\Omega \end{array}$$

***Case 6 (Static Shift).*** Assume

$$\frac{A[\boldsymbol{k} : \tau/\delta \to \alpha/\delta], \sigma \vdash \boldsymbol{M} : \sigma, \beta\ [\boldsymbol{W}]}{A, \alpha \vdash \boldsymbol{\xi k.\ M} : \tau, \beta\ [\overline{\boldsymbol{\xi}}\boldsymbol{k.\ W}]}$$

We need to show

$$(\langle(\lambda v.\, K)\,(\mathcal{P}\,[\![\overline{\boldsymbol{\xi}}\boldsymbol{k.\ W}]\!]\,\rho)\rangle, \langle(\lambda v'.\, K')\,(\mathcal{I}\,[\![\boldsymbol{\xi k.\ M}]\!]\,\rho')\rangle) \in R_\beta$$

assuming $(\rho, \rho') \models A$ and $(\lambda v.\, K, \lambda v'.\, K') \models \tau \rightsquigarrow \alpha$. From

$$\begin{array}{rcl}\langle(\lambda v.\, K)\,(\mathcal{P}\,[\![\overline{\boldsymbol{\xi}}\boldsymbol{k.\ W}]\!]\,\rho)\rangle & = & \langle(\lambda v.\, K)\,(\xi k.\,\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho[k/\boldsymbol{k}])\rangle \\ & \sim & \langle\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho[\lambda a.\,\langle(\lambda v.\, K)\,a\rangle/\boldsymbol{k}]\rangle \\ & \sim & \langle(\lambda x.\, x)\,(\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho[\lambda a.\,\langle(\lambda v.\, K)\,a\rangle/\boldsymbol{k}])\rangle\end{array}$$

and

$$\begin{array}{rcl}\langle(\lambda v'.\, K')\,(\mathcal{I}\,[\![\boldsymbol{\xi k.\ M}]\!]\,\rho')\rangle & = & \langle(\lambda v'.\, K')\,(\xi k.\,\mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho'[k/\boldsymbol{k}])\rangle \\ & \sim & \langle\mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho'[\lambda a'.\,\langle(\lambda v'.\, K')\,a'\rangle/\boldsymbol{k}]\rangle \\ & \sim & \langle(\lambda x.\, x)\,(\mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho'[\lambda a'.\,\langle(\lambda v'.\, K')\,a'\rangle/\boldsymbol{k}])\rangle\end{array}$$

we have:

$$\begin{array}{rl} & (\langle(\lambda v.\, K)\,(\mathcal{P}\,[\![\overline{\boldsymbol{\xi}}\boldsymbol{k.\ W}]\!]\,\rho)\rangle, \langle(\lambda v'.\, K')\,(\mathcal{I}\,[\![\boldsymbol{\xi k.\ M}]\!]\,\rho')\rangle) \in R_\beta \\ \iff & (\langle(\lambda x.\, x)\,(\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho[\lambda a.\,\langle(\lambda v.\, K)\,a\rangle/\boldsymbol{k}])\rangle, \langle(\lambda x.\, x)\,(\mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho'[\lambda a'.\,\langle(\lambda v'.\, K')\,a'\rangle/\boldsymbol{k}])\rangle) \in R_\beta\end{array}$$

Since $(\lambda x.\, x, \lambda x.\, x) \models \sigma \rightsquigarrow \sigma$, we are done by the induction hypothesis if we can prove

$$(\rho[\lambda a.\,\langle(\lambda v.\, K)\,a\rangle/\boldsymbol{k}], \rho'[\lambda a'.\,\langle(\lambda v'.\, K')\,a'\rangle/\boldsymbol{k}]) \models A[\boldsymbol{k} : \tau/\delta \to \alpha/\delta]$$

or in other words,

$$(\lambda a.\,\langle(\lambda v.\, K)\,a\rangle, \lambda a'.\,\langle(\lambda v'.\, K')\,a'\rangle) \in R_{\tau/\delta \to \alpha/\delta}\ .$$

So take any $(V_1, V_1') \in R_\tau$ and $(\lambda u.\, L, \lambda u'.\, L')$ such that $(\lambda u.\, L, \lambda u'.\, L') \models \alpha \rightsquigarrow \delta$. We need to prove

$$(\langle(\lambda u.\, L)\,\langle(\lambda v.\, K)\,V_1\rangle\rangle, \langle(\lambda u'.\, L')\,\langle(\lambda v'.\, K')\,V_1'\rangle\rangle) \in R_\delta$$

which holds since $(\lambda v.\, K, \lambda v'.\, K') \models \tau \rightsquigarrow \alpha$.

***Case 7 (Dynamic Shift).*** Assume

$$\frac{A[\boldsymbol{k} : d], \sigma \vdash \boldsymbol{M} : \sigma, \beta\ [\boldsymbol{W}]}{A, d \vdash \boldsymbol{\xi k.\ M} : d, \beta\ [\underline{\boldsymbol{\xi}}\boldsymbol{k.\ W}]}$$

We need to show

$$(\langle(\lambda v.\, K)\,(\mathcal{P}\,[\![\underline{\boldsymbol{\xi}}\boldsymbol{k.\ W}]\!]\,\rho)\rangle, \langle(\lambda v'.\, K')\,(\mathcal{I}\,[\![\boldsymbol{\xi k.\ M}]\!]\,\rho')\rangle) \in R_\beta$$

assuming $(\rho, \rho') \models A$ and $(\lambda v.\, K, \lambda v'.\, K') \models d \rightsquigarrow d$. From

$$\begin{array}{rcl}\langle(\lambda v.\, K)\,(\mathcal{P}\,[\![\underline{\boldsymbol{\xi}}\boldsymbol{k.\ W}]\!]\,\rho)\rangle & = & \langle(\lambda v.\, K)\,(\xi k.\,\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho[\boldsymbol{\lambda v^\diamond.}\,\langle k\,\boldsymbol{v^\diamond}\rangle/\boldsymbol{k}])\rangle \\ & \sim & \langle\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho[\boldsymbol{\lambda v^\diamond.}\,\langle(\lambda a.\,\langle(\lambda v.\, K)\,a\rangle)\,\boldsymbol{v^\diamond}\rangle/\boldsymbol{k}]\rangle \\ & \sim & \langle\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho[\boldsymbol{\lambda v^\diamond.}\,\langle\langle(\lambda v.\, K)\,\boldsymbol{v^\diamond}\rangle\rangle/\boldsymbol{k}]\rangle \\ & \sim & \langle\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho[\boldsymbol{\lambda v^\diamond.}\,\langle(\lambda v.\, K)\,\boldsymbol{v^\diamond}\rangle/\boldsymbol{k}]\rangle \\ & \sim & \langle(\lambda x.\, x)\,(\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho[\boldsymbol{\lambda v^\diamond.}\,\langle(\lambda v.\, K)\,\boldsymbol{v^\diamond}\rangle/\boldsymbol{k}])\rangle\end{array}$$

and

$$\begin{array}{rcl}\langle(\lambda v'.\, K')\,(\mathcal{I}\,[\![\boldsymbol{\xi k.\ M}]\!]\,\rho')\rangle & = & \langle(\lambda v'.\, K')\,(\xi k.\,\mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho'[k/\boldsymbol{k}])\rangle \\ & \sim & \langle\mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho'[\lambda v^\diamond.\,\langle(\lambda v'.\, K')\,v^\diamond\rangle/\boldsymbol{k}]\rangle \\ & \sim & \langle(\lambda x.\, x)\,(\mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho'[\lambda v^\diamond.\,\langle(\lambda v'.\, K')\,v^\diamond\rangle/\boldsymbol{k}])\rangle\end{array}$$

we have:

$$\begin{array}{ll} & (\langle \lambda v.\, K\,(\mathcal{P}\,[\![\boldsymbol{\xi k.\, W}]\!]\,\rho)\rangle, \langle \lambda v'.\, K'\,(\mathcal{I}\,[\![\boldsymbol{\xi k.\, M}]\!]\,\rho')\rangle) \in R_\beta \\ \iff & (\langle (\lambda x.\, x)\,(\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho[\boldsymbol{\lambda v^\diamond.}\,\langle (\lambda v.\, K)\,\boldsymbol{v^\diamond}\rangle/\boldsymbol{k}])\rangle, \langle (\lambda x.\, x)\,(\mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho'[\lambda v^\diamond.\,\langle (\lambda v'.\, K')\,v^\diamond\rangle/\boldsymbol{k}])\rangle) \in R_\beta \end{array}$$

Since $(\lambda x.\, x, \lambda x.\, x) \models \sigma \rightsquigarrow \sigma$, we are done by the induction hypothesis if we can prove

$$(\rho[\boldsymbol{\lambda v^\diamond.}\,\langle (\lambda v.\, K)\,\boldsymbol{v^\diamond}\rangle/\boldsymbol{k}], \rho'[\lambda v^\diamond.\,\langle (\lambda v'.\, K')\,v^\diamond\rangle/\boldsymbol{k}]) \models A[\boldsymbol{k} : d]$$

or in other words,

$$(\boldsymbol{\lambda v^\diamond.}\,\langle (\lambda v.\, K)\,\boldsymbol{v^\diamond}\rangle, \lambda v^\diamond.\,\langle (\lambda v'.\, K')\,v^\diamond\rangle) \in R_d \ .$$

Now, $(\boldsymbol{v^\diamond}, v^\diamond) \in R_d$ holds, so we have $(\langle (\lambda v.\, K)\,\boldsymbol{v^\diamond}\rangle, \langle (\lambda v'.\, K')\,v^\diamond\rangle) \in R_d$ since $(\lambda v.\, K, \lambda v'.\, K') \models d \rightsquigarrow d$, that is,

$$\mathcal{I}\,[\![\langle (\lambda v.\, K)\,\boldsymbol{v^\diamond}\rangle]\!]\,\rho_{id} \quad \sim \quad \langle (\lambda v'.\, K')\,v^\diamond\rangle \tag{2}$$

To obtain $(\boldsymbol{\lambda v^\diamond.}\,\langle (\lambda v.\, K)\,\boldsymbol{v^\diamond}\rangle, \lambda v^\diamond.\,\langle (\lambda v'.\, K')\,v^\diamond\rangle) \in R_d$, we calculate:

$$\begin{array}{rcll} \mathcal{I}\,[\![\boldsymbol{\lambda v^\diamond.}\,\langle (\lambda v.\, K)\,\boldsymbol{v^\diamond}\rangle]\!]\,\rho_{id} & = & \lambda v^\diamond.\,\mathcal{I}\,[\![\langle (\lambda v.\, K)\,\boldsymbol{v^\diamond}\rangle]\!]\,\rho_{id}[v^\diamond/\boldsymbol{v^\diamond}] & \text{definition of } \mathcal{I} \\ & = & \lambda v^\diamond.\,\mathcal{I}\,[\![\langle (\lambda v.\, K)\,\boldsymbol{v^\diamond}\rangle]\!]\,\rho_{id} & \text{definition of } \rho_{id} \\ & \sim & \lambda v^\diamond.\,\langle (\lambda v'.\, K')\,v^\diamond\rangle & \text{Equation (2)} \end{array}$$

***Case 8 (Reset).*** Assume

$$\frac{A, \sigma \vdash \boldsymbol{M} : \sigma, \tau\ [\boldsymbol{W}]}{A, \alpha \vdash \boldsymbol{\langle M \rangle} : \tau, \alpha\ [\overline{\boldsymbol{\langle W \rangle}}]}$$

We need to show

$$(\langle (\lambda v.\, K)\,(\mathcal{P}\,[\![\overline{\boldsymbol{\langle W \rangle}}]\!]\,\rho)\rangle, \langle (\lambda v'.\, K')\,(\mathcal{I}\,[\![\boldsymbol{\langle M \rangle}]\!]\,\rho')\rangle) \in R_\alpha$$

assuming $(\rho, \rho') \models A$ and $(\lambda v.\, K, \lambda v'.\, K') \models \tau \rightsquigarrow \alpha$. From the definition of $\mathcal{P}$ and $\mathcal{I}$, we have:

$$\begin{array}{ll} & (\langle (\lambda v.\, K)\,(\mathcal{P}\,[\![\overline{\boldsymbol{\langle W \rangle}}]\!]\,\rho)\rangle, \langle (\lambda v'.\, K')\,(\mathcal{I}\,[\![\boldsymbol{\langle M \rangle}]\!]\,\rho')\rangle) \in R_\alpha \\ \iff & (\langle (\lambda v.\, K)\,\langle \mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho\rangle\rangle, \langle (\lambda v'.\, K')\,\langle \mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho'\rangle\rangle) \in R_\alpha \\ \iff & (\langle (\lambda v.\, K)\,\langle (\lambda x.\, x)\,(\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho)\rangle\rangle, \langle (\lambda v'.\, K')\,\langle (\lambda x.\, x)\,(\mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho')\rangle\rangle) \in R_\alpha \end{array}$$

From $(\lambda v.\, K, \lambda v'.\, K') \models \tau \rightsquigarrow \alpha$, it suffices to show

$$(\langle (\lambda x.\, x)\,(\mathcal{P}\,[\![\boldsymbol{W}]\!]\,\rho)\rangle, \langle (\lambda x.\, x)\,(\mathcal{I}\,[\![\boldsymbol{M}]\!]\,\rho')\rangle) \in R_\tau$$

which holds by the induction hypothesis since $(\lambda x.\, x, \lambda x.\, x) \models \sigma \rightsquigarrow \sigma$.

This completes the cases for the proof. □